Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s

Modelis: UDM-Pro-Max

Gamintojas: UBIQUITI

EAN: 810084693254

Prekės kodas: 365506

592.98€

Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN (RJ-45) ports: 9 | Routing protocols: BGP | Cables included: AC | Processor model: Cortex-A57 | Operating temperature (T-T): -10 - 40 °C | Height: 43.7 mm | DC input voltage: 12 V | Weight: 4.7 kg | Power consumption (max): 60 W | Processor frequency: 2000 MHz | Display type: LCM | Reset button: Yes | Processor family: ARM Cortex | Control display unit: Yes | Rack capacity: 1U | Number of processors installed: 1 | Input frequency: 50/60 Hz | Firewall security: Yes | Flash memory: 32000 MB | Built-in processor: Yes | VLAN support: Yes | DHCP server: Yes | Operating relative humidity (H-H): 5 - 95% | Ethernet LAN data rates: 2500 | Depth: 285.6 mm | Multicast support: Yes | Product colour: Grey | Mounting type: Rack mounting | Internal memory: 8000 MB | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): No | WAN connection: Ethernet (RJ-45), SFP+ | SSD capacity: 128 GB | Routing protocols: OSPF | Width: 442.4 mm | LED indicators:

Error | LED indicators: Link | Input voltage: 100 - 240 V | LED indicators: Activity | Processor manufacturer: ARM | Heat dissipation: 205 BTU/h | Input current: 2 A | LED indicators: Ready | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Federal Communications Commission (FCC) | Enclosure material: Aluminium/SGCC | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Electromagnetic (EMP) protection (contact): 8 kV | Electromagnetic (EMP) protection (air): 15 kV | Electrostatic Discharge (ESD) protection (contact): 8 kV | Warnings: Do not use in damp conditions. | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Electrostatic Discharge (ESD) protection (air): 15 kV | Port aggregation: Yes | SFP+ ports quantity: 2 | Electromagnetic (EMP) protection: Yes