



TP-Link TL-SF1005D Managed Fast Ethernet (10/100) White



Modelis: TL-SF1005D

Gamintojas: TP-LINK

EAN: 6935364020064

Prekės kodas: 365641

13.00€

Certification: FCC, RoHS | Package weight: 190 g | AC input frequency: 50 Hz | Web-based management: Yes | AC input voltage: 220 V | Ethernet LAN data rates: 10,100 Mbit/s | Networking standards: IEEE 802.3x | LED indicators: Yes | Input current: 0.6 A | Product colour: White | Networking standards: IEEE 802.3u | Package type: Box | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Power consumption (max): 1.87 W | Storage relative humidity (H-H): 5 - 90% | Store-and-forward: Yes | Power consumption (typical): 1.87 W | Switch type: Managed | Full duplex: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 108 mm | Switching capacity: 1.6 Gbit/s | Auto-negotiation: Yes | Heat dissipation: 6.38 BTU/h | Operating

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

relative humidity (H-H): 10 - 90% | User guide: Yes | AC adapter included: Yes | Package width: 91 mm | Power over Ethernet (PoE): No | Width: 103.5 mm | Rack mounting: No | Power connector: DC-in jack | Operating temperature (T-T): 0 - 40 °C | Power source: DC | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Cables included: AC | 10G support: No | Depth: 70 mm | Supported network protocols: CSMA/CD, TCP/IP | Power supply included: No | Auto MDI/MDI-X: Yes | MAC address table: 1000 entries | Flow control support: Yes | Height: 22 mm | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Package height: 85 mm | Sustainability compliance: Yes | Spanning tree protocol: Yes | Fast Ethernet (copper) ports quantity: 5 | DC input voltage: 5 V | Fanless: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903