



TP-Link 24-Port Gigabit Desktop/Rackmount Network Switch



Modelis: TL-SG1024D

Gamintojas: TP-LINK

EAN: 6935364020620

Prekės kodas: 365642

91.98€

Certification: FCC, CE, RoHS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Rack mounting: Yes | Connectivity LEDs: Y | Basic switching RJ-45 Ethernet ports quantity: 24 | Forwarding rate: 35.7 Mpps | Switching capacity: 48 Gbit/s | Power requirements: 100 - 240V, 50/60Hz | Supported network protocols: CSMA/CD, TCP/IP | Stackable: Yes | Harmonized System (HS) code: 85176990 | Power connector: DC-in jack | Full duplex: Yes | Auto MDI/MDI-X: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Operating temperature (T-T): 32 - 104 °F | Rack mount kit: Yes | Height: 44 mm | Bandwidth: 48 Gbit/s | 10G support: No | Jumbo frames: 10000 | Cable types supported: Cat5 | Cable types supported: Cat5e | Maximum data transfer rate: 1 Gbit/s | Heat dissipation: 46.44 BTU/h | Switch type: Unmanaged | Cable types supported: Cat4 | Power supply included: Yes | Supported data transfer rates: 10/100/100 Mbps | Flow control support: Yes | Cable types supported: Cat3 | Jumbo frames support: Yes | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Product colour: Grey | Package weight: 1.95 kg | Connectivity technology: Wired | User guide: Yes | Package type: Box | Package height: 80 mm | Cables included: AC | Storage relative humidity (H-H): 5 - 90% | LED indicators: Yes | AC input voltage: 100 - 240 V |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power over Ethernet (PoE): No | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power consumption (max): 13.62 W | Power source: AC | Networking features: Gigabit Ethernet | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u | Operating temperature (T-T): 0 - 40 °C | Package width: 250 mm | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50 - 60 Hz | Dimensions (WxDxH): 294 x 180 x 44 mm | Package depth: 400 mm | Width: 294 mm | Depth: 180 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903