



## TP-Link 24-Port Gigabit Easy Smart Switch



Modelis: TL-SG1024DE

Gamintojas: TP-LINK

EAN: 6935364021245

Prekės kodas: 365647

# 108.98€

Certification: FCC, CE, RoHS | Compatible operating systems: Windows 98SE, NT, 2000, XP, Vista, Windows 7, Windows 8, MAC OS, NetWare, UNIX, Linux | 10G support: No | Power supply included: Yes | Rate limiting: Yes | Operating relative humidity (H-H): 10 - 90% | Rack mount kit: Yes | Harmonized System (HS) code: 85176990 | Switch layer: L2 | Rack mounting: Yes | Port mirroring: Yes | Form factor: 1U | Product colour: Black | Cable types supported: Cat6 | Width: 294 mm | Number of VLANs: 32 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power source: AC | User guide: Yes | Cable types supported: Cat3 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 1000BASE-T | Power consumption (max): 14.86 W | Package type: Box | Basic switching RJ-45 Ethernet ports quantity: 24 | Forwarding rate: 35.7 Mpps | Link aggregation: Yes | Switching capacity: 48 Gbit/s | AC input frequency: 50 - 60 Hz | Package weight: 2.02 kg | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Gigabit Ethernet (copper) ports quantity: 24 | Jumbo frames support: Yes | Jumbo frames: 9216 | Depth: 180 mm | Virtual LAN features: Port-based VLAN | Broadcast storm control: Yes | IGMP

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

snooping: Yes | Package width: 250 mm | Auto MDI/MDI-X: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Operating temperature (T-T): 0 - 40 °C | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 0.512 MB | Package height: 80 mm | Switch type: Managed | LED indicators: Yes | Number of queues: 4 | Cables included: AC | Height: 44 mm | Cable types supported: Cat5 | Heat dissipation: 114.37 BTU/h | Loop protection: Yes | Virtual LAN features: Tagged VLAN | AC input voltage: 100 - 240 V | Copper ethernet cabling technology: 100BASE-TX | Storage relative humidity (H-H): 5 - 90% | VLAN support: Yes | Package depth: 400 mm | Flow control support: Yes

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903