



NETGEAR GS308-300PES network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Black

Modelis: GS308-300PES

Gamintojas: NETGEAR

EAN: 606449140149

Prekės kodas: 365683

30.99€

Certification: CE Mark FCC Part 15 Class B IC Class B RCM CCC VCCI KC | Operating temperature (T-T): 0 - 40 °C | Product colour: Black | LED indicators: Activity | Operating relative humidity (H-H): 0 - 90% | Quality of Service (QoS) support: Yes | Operating altitude: 0 - 3000 m | LED indicators: Power | Storage temperature (T-T): -20 - 70 °C | LED indicators: Link | Depth: 101 mm | Weight: 390 g | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power consumption (max): 3.04 W | Networking standards: IEEE 802.3u | Power over Ethernet (PoE): No | Width: 158 mm | Mean time between failures (MTBF): 3711898 h | Height: 29 mm | Copper ethernet cabling technology: 1000BASE-T | Warranty period: 3 year(s) | Warnings: Electronic devices should

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

be recycled in accordance with local regulations. | Warnings: Do not use the device in damp conditions to avoid a short circuit. | Harmonized System (HS) code: 85176990 | Packet buffer memory: 128 MB | MAC address table: 8000 entries | Auto MDI/MDI-X: Yes | Jumbo frames support: Yes | Copper ethernet cabling technology: 10BASE-T | Warnings: Do not open the housing of the unit due to the risk of electric shock. | Rack mounting: No | Flow control support: Yes | Switching capacity: 16 Gbit/s | Copper ethernet cabling technology: 100BASE-TX | Power connector: DC-in jack | Jumbo frames: 9216 | Shipping (inner) case length: 32.9 cm | Shipping (inner) case net weight: 14.6 kg | Switch layer: L2 | Housing material: Metal | Shipping (inner) case height: 43.4 cm | Heat dissipation: 10.4 BTU/h | Switch type: Unmanaged | Auto-sensing: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Forwarding rate: 1.448 Mpps | Wall mountable: Yes | Latency (1 Gbps): 2.6 μ s | Products per shipping (inner) case: 20 pc(s) | Gigabit Ethernet (copper) ports quantity: 8 | Cable length detection: Yes | 10G support: No | Shipping (inner) case width: 48.6 cm | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000)