



NETGEAR GS724TP- 300EUS network switch Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue

Modelis: GS724TP-300EUS

Gamintojas: NETGEAR

EAN: 606449162660

Prekės kodas: 365691

332.99€

Certification: CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC | Web-based management: Yes | Jumbo frames support: Yes | MAC address filtering: Yes | Security algorithms: HTTPS | Operating relative humidity (H-H): 0 - 90% | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1as | Power supply included: Yes | Power consumption (max): 446.7 W | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.1p | Storage relative humidity (H-H): 0 - 95% | Weight: 3.7 kg | Switching capacity: 52 Gbit/s | Operating temperature (T-T): 0 - 50 °C | Quick start guide: Yes | Jumbo frames: 9216 | Link aggregation: Yes | Spanning tree protocol: Yes | Store-and-forward: Yes | Number of fans: 3 fan(s) | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Manual: Yes | Fiber ethernet cabling technology: 1000BASE-SX | Firmware upgradeable: Yes | 10G support: Yes | Number of queues: 8 | Cables included: AC | Total Power over Ethernet (PoE) budget: 380 W | Quality of Service (QoS) support: Yes | Switch type: Managed | Storage temperature (T-T): -20 - 70 °C | LED indicators: Activity | Access Control List (ACL): Yes | Packet buffer memory: 0.512 MB | Fiber ethernet cabling technology: 1000BASE-LX | Number of static routes: 32 | Number of VLANs: 64 | User guide: Yes | SSH/SSL support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-T | SFP module slots quantity: 2 | Broadcast storm control: Yes | Width: 440 mm | Mean time between failures (MTBF): 634966 h | System event log: Yes | AC input voltage: 100 - 240 V | LED indicators: Link | MAC address table: 8000 entries | Full duplex: Yes | Height: 43 mm | Port mirroring: Yes | IGMP snooping: Yes | Switch layer: L2/L3/L4 | IP routing: Yes | DHCP features: DHCP client | Operating altitude: 0 - 3000 m | Product colour: Blue | VLAN support: Yes | Number of multicast groups filtered: 128 | Power connector: DC-in jack | LED indicators: Speed | Power over Ethernet (PoE): Yes | Rack mounting: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Management protocols: SNMP v1/v2/v3 | Multicast support: Yes | Flow control support: Yes | Stackable: Yes | Depth: 204 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903