



NETGEAR GS728TP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Modelis: GS728TP-300EUS

Gamintojas: NETGEAR

EAN: 606449162257

Prekės kodas: 365693

357.99€

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Access Control List (ACL) IPv4 entries: 100 | Flash memory: 64 MB | Warnings: Make sure the ventilation of the equipment is not blocked. | Redundant fans support: Yes | Warnings: Avoid contact of the device with liquid. | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Processor model: ARM Cortex-A55 | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Packet buffer memory: 1.5 MB | Latency (1 Gbps): 4.691 μ s | Rack mounting: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| ARP inspection: Yes | Power over Ethernet (PoE): Yes | Switching capacity: 56 Gbit/s | Width: 440 mm | Operating relative humidity (H-H): 0 - 90% | Built-in processor: Yes | Power over Ethernet plus (PoE+) ports quantity: 24 | Noise level: 26.8 dB | Port mirroring: Yes | DHCP features: DHCP snooping | Power consumption (max): 226 W | Depth: 257 mm | MAC address table: 16000 entries | Latency (10-100 Mbps): 8.864 μ s | Power source: AC | Switch layer: L2/L3/L4 | DHCP features: DHCPv6 client | Number of fans: 2 fan(s) | Height: 432 mm | Power over Ethernet (PoE) power per port: 190 W | Storage relative humidity (H-H): 0 - 95% | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | USB Type-A ports quantity: 1 | Storage temperature (T-T): -20 - 70 °C | Internal memory: 512 MB | Number of VLANs: 256 | Multicast support: Yes | Power consumption (typical): 24 W | Access Control List (ACL): Yes | Switch type: Managed | Heat dissipation: 772.9 BTU/h | Mean time between failures (MTBF): 1751613 h | Processor manufacturer: ARM | Installed SFP modules quantity: 4 | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Operating temperature (T-T): 0 - 50 °C | Product colour: Grey | IPv4 routes: 32 | Processor frequency: 800 MHz | Weight: 3.78 kg | IPv6 routes: 32

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903