



**NETGEAR
GS728TPP
Managed
L2/L3/L4 Gigabit
Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**

Modelis: GS728TPP-300EUS

Gamintojas: NETGEAR

EAN: 606449162356

Prekės kodas: 365694

458.99€

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power over Ethernet (PoE) power per port: 380 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | DHCP features: DHCP snooping | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Power source: AC | Switch layer: L2/L3/L4 | Latency (10-100 Mbps): 8.871 μs | DHCP features: DHCPv6 client | Redundant fans support: Yes | Height: 432 mm | Power over

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Ethernet (PoE): Yes | Width: 440 mm | Access Control List (ACL) IPv4 entries: 100 | Flash memory: 64 MB | VLAN support: Yes | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.1w | Processor model: ARM Cortex-A55 | Rack mounting: Yes | ARP inspection: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Product colour: Grey | Built-in processor: Yes | Latency (1 Gbps): 4.701 μ s | Noise level: 33.3 dB | MAC address table: 16000 entries | Operating temperature (T-T): 0 - 50 °C | Access Control List (ACL): Yes | Processor manufacturer: ARM | Number of fans: 2 fan(s) | Processor frequency: 800 MHz | Power over Ethernet plus (PoE+) ports quantity: 24 | Operating relative humidity (H-H): 0 - 90% | Weight: 4.11 kg | Power consumption (max): 427 W | Packet buffer memory: 1.5 MB | Storage temperature (T-T): -20 - 70 °C | Internal memory: 512 MB | Number of VLANs: 256 | Mean time between failures (MTBF): 1252990 h | Switching capacity: 56 Gbit/s | Power consumption (typical): 26 W | Switch type: Managed | Installed SFP modules quantity: 4 | Depth: 257 mm | Multicast support: Yes | USB Type-A ports quantity: 1 | IPv6 routes: 32 | IPv4 routes: 32

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903