



NETGEAR GS108Tv3 Managed L2 Gigabit Ethernet (10/100/1000) Grey

Modelis: GS108T-300PES

Gamintojas: NETGEAR

EAN: 606449138634

Prekės kodas: 365697

89.00€

Certification: CE, FCC, VCCI Class B, C-Tick | Multicast support: Yes | DHCP features: DHCP client | Switch layer: L2 | Stackable: No | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | Master (outer) case height: 312 mm | Memory type: RAM | Master (outer) case width: 214 mm | Non-operating altitude: 0 - 3000 m | Management protocols: SNMP | Harmonized System (HS) code: 85176990 | Master (outer) case gross weight: 5.49 kg | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Link aggregation: Yes | Broadcast storm control: Yes | IPv4 multicast entries: 32 | Access Control List (ACL) IPv6 entries: 100 | Power supply included: Yes | Switching protocols: SNMP | Full duplex: Yes | Flow control support: Yes | Rate limiting: Yes | DC input voltage: 54 V | Power connector: DC-in jack | Switching capacity: 16 Gbit/s | Jumbo frames support: Yes | Spanning tree protocol: Yes | MAC address auto-learning supported: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Number of multicast groups filtered: 256 | Master (outer) case length:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

474 mm | IGMP snooping: Yes | MAC address table: 8000 entries | Packet buffer memory: 0.5 MB | Store-and-forward: Yes | Port mirroring: Yes | Number of VLANs: 64 | Switch type: Managed | Heat dissipation: 18.66 BTU/h | Access Control List (ACL): Yes | Mean time between failures (MTBF): 2388657 h | Package weight: 780 g | LED indicators: Speed | LED indicators: LAN | LED indicators: Power | Operating temperature (T-T): 0 - 40 °C | AC input frequency: 50 - 60 Hz | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 0 - 95% | Power over Ethernet (PoE): No | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3ad | Manual: Yes | Operating altitude: 0 - 3000 m | Networking standards: IEEE 802.3x | AC input voltage: 100 - 240 V | LED indicators: Link | Width: 158 mm | Firmware upgradeable: Yes | LED indicators: Activity | LED indicators: PoE | Height: 27 mm | Package width: 226 mm | Operating relative humidity (H-H): 0 - 95% | Input current: 1.25 A | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Products per master (outer) case: 6 pc(s) | Power consumption (max): 5.5 W | Internal memory: 128 MB | Package depth: 270 mm | Quality of Service (QoS) support: Yes | Product colour: Grey | Package height: 64 mm | Storage temperature (T-T): -20 - 70 °C | Processor frequency: 500 MHz | Copper ethernet cabling technology: 10BASE-T | Weight: 430 g | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-TX | Package type: Box | Flash memory: 32 MB | Supported network protocols: HTTP, HTTPS | Depth: 101 mm | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903