



# NETGEAR GS110TP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Modelis: GS110TP-300EUS

Gamintojas: NETGEAR

EAN: 606449137644

Prekės kodas: 365698

## 160.99€

Certification: CE, FCC, VCCI Class B, C-Tick | Power consumption (max): 15.1 W | Number of VLANs: 64 | Quality of Service (QoS) support: Yes | Master (outer) case gross weight: 9.73 kg | Port mirroring: Yes | Weight: 610 g | Internal memory: 128 MB | Package height: 86 mm | Number of multicast groups filtered: 256 | Operating temperature (T-T): 0 - 40 °C | Basic switching RJ-45 Ethernet ports quantity: 8 | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | IGMP snooping: Yes | SFP module slots quantity: 2 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Power over Ethernet (PoE): Yes | Rack mounting: No | Master (outer) case height: 309 mm | Width: 236 mm | Jumbo frames support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Link aggregation: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Package type: Box | Networking standards: IEEE 802.3x | LED indicators: Power | LED indicators: Speed | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 0 - 95% | Manual: Yes | Processor frequency: 500 MHz | AC input voltage: 100 - 240 V | LED indicators: Link | MAC address table: 8000 entries | Package weight: 1.49 kg | Memory type: RAM | Rate limiting: Yes | Package width: 161 mm | LED indicators: LAN | Switch layer: L2/L3/L4 | Operating altitude: 0 - 3000 m | Mean time between failures (MTBF): 1200041 h | DC input voltage: 54 V | Spanning tree protocol: Yes | Networking standards: IEEE 802.3ab | Heat dissipation: 237.38 BTU/h | Switch type: Managed | Total Power over Ethernet (PoE) budget: 69.5 W | Product colour: Grey | Storage temperature (T-T): -20 - 70 °C | LED indicators: Activity | Access Control List (ACL): Yes | Packet buffer memory: 0.5 MB | Master (outer) case width: 274 mm | Package depth: 267 mm | Height: 27 mm | Networking standards: IEEE 802.3z | Power supply included: Yes | Switching protocols: SNMP | LED indicators: PoE | Non-operating altitude: 0 - 3000 m | Management protocols: SNMP | ARP inspection: Yes | DHCP features: DHCP client | Full duplex: Yes | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.3u | IPv4 multicast entries: 32 | Access Control List (ACL) IPv6 entries: 100 | Store-and-forward: Yes | Broadcast storm control: Yes | Input current: 1.25 A | Harmonized System (HS) code: 85176990 | Flow control support: Yes | Products per master (outer) case: 6 pc(s) | Networking standards: IEEE 802.3af | Power over Ethernet (PoE) power per port: 55 W | Switching capacity: 20 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | Multicast support: Yes | Supported network protocols: HTTP, HTTPS | Depth: 101 mm | Master (outer) case length: 350 mm

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903