



NETGEAR 52- Port PoE Gigabit/10G Stackable Smart Switch (GS752TXP)



Modelis: GS752TXP-300EUS

Gamintojas: NETGEAR

EAN: 606449171181

Prekės kodas: 365701

802.99€

Product colour: Black | MAC address filtering: Yes | Broadcast storm control: Yes | Port mirroring: Yes | Power source: AC | Spanning tree protocol: Yes | Operating temperature (T-T): 0 - 50 °C | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 380 W | Width: 440 mm | Rack mounting: Yes | Power over Ethernet plus (PoE+) ports quantity: 48 | VLAN support: Yes | Weight: 5.54 kg | Built-in processor: Yes | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | Full duplex: Yes | Networking standards: IEEE 802.1x | Height: 43 mm | Depth: 345 mm | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Virtual LAN features: Voice VLAN | Networking standards: IEEE 802.1as | Rate limiting: Yes | Link aggregation: Yes | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

static routes: 32 | DHCP features: DHCP client | Stackable: Yes | Non-operating altitude: 0 - 3000 m | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Power consumption (max): 51 W | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Flash memory: 64 MB | Switch layer: L2/L3/L4 | Packet buffer memory: 16 MB | MAC address table: 16000 entries | Noise level: 36.6 dB | Static route: Yes | 10G support: Yes | SSH/SSL support: Yes | Flow control support: Yes | Storage temperature (T-T): -20 - 70 °C | Latency (10 Gbps): 4.107 μs | Operating relative humidity (H-H): 0 - 95% | Heat dissipation: 2944.6 BTU/h | Switch type: Managed | Operating altitude: 0 - 3000 m | Mean time between failures (MTBF): 1296949 h | Power supply included: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903