



NETGEAR 8x1G PoE+ 110W 1x1G and 1xSFP Managed Switch



Modelis: GSM4210PD-100EUS

Gamintojas: NETGEAR

EAN: 606449160192

Prekės kodas: 365702

777.99€

Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Processor frequency: 1250 MHz | Weight: 967 g | User guide: Yes | SSH/SSL support: Yes | Authentication: MAC-based authentication | Product colour: Black | Internal memory: 2048 MB | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1D | Power over Ethernet plus (PoE+) ports quantity: 8 | Manual: Yes | Authentication type: RADIUS | Operating relative humidity (H-H): 0 - 90% | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bt | Storage temperature (T-T): -20 - 70 °C | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 0 - 95% | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Switching capacity: 24 Gbit/s | IPv4 multicast entries: 2000 | AC input frequency: 50 - 60 Hz | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Rate limiting: Yes | Loop protection: Yes | DHCP features: DHCPv6 snooping | DHCP features: DHCPv6 client | Total Power over

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Ethernet (PoE) budget: 110 W | Link aggregation: Yes | DHCP features: DHCPv6 relay | Full duplex: Yes | DHCP features: DHCP Option 82 | Switch layer: L2/L3 | Operating temperature (T-T): 0 - 50 °C | Noise level: 30.06 dB | Networking standards: IEEE 802.3af | Rack mounting: Yes | IGMP snooping: Yes | Built-in processor: Yes | Operating altitude: 0 - 3000 m | Store-and-forward: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Multicast support: Yes | DHCP features: DHCP snooping | Spanning tree protocol: Yes | Height: 40 mm | Depth: 140 mm | BPDU filtering/protection: Yes | Processor model: ARM Cortex-A9 | DHCP features: DHCP relay | Power over Ethernet (PoE): Yes | Power supply included: Yes | MAC address table: 16000 entries | DHCP features: DHCP server | LED indicators: Status | Width: 210 mm | Power source: AC/DC | Broadcast storm control: Yes | DHCP features: DHCPv6 server | LED indicators: Power | LED indicators: PoE | Heat dissipation: 559.555 BTU/h | AC input voltage: 220 - 240 V | Access Control List (ACL): Yes | Switch type: Managed | Non-operating altitude: 0 - 3000 m