



NETGEAR GS748Tv6 Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Black, Grey

Modelis: GS748T-600EUS

Gamintojas: NETGEAR

EAN: 606449169218

Prekės kodas: 365704

487.99€

Certification: CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1as | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Cables included: AC | Operating temperature (T-T): 0 - 40 °C | Number of queues: 8 | LED indicators: Activity | Access Control List (ACL): Yes | MAC address table: 16000 entries | Operating altitude: 0 - 3000 m | LED indicators: Power | IP routing: Yes | Mean time between failures (MTBF): 390728 h | Switch type: Managed | Web-based management: Yes | MAC address filtering: Yes | Switch layer: L2/L3/L4 | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Full duplex: Yes | Height: 43 mm | Networking standards: IEEE 802.3i | Port mirroring:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Yes | AC input voltage: 100 - 240 V | LED indicators: Link | System event log: Yes | Power over Ethernet (PoE): No | Width: 440 mm | DHCP features: DHCP client | SFP module slots quantity: 2 | VLAN support: Yes | Storage relative humidity (H-H): 0 - 95% | Copper ethernet cabling technology: 1000BASE-T | Basic switching RJ-45 Ethernet ports quantity: 48 | Spanning tree protocol: Yes | Combo SFP ports quantity: 2 | Quality of Service (QoS) support: Yes | Manual: Yes | IGMP snooping: Yes | Noise level: 37.2 dB | Rack mounting: Yes | Product colour: Grey | Product colour: Black | Non-operating altitude: 0 - 3000 m | Security algorithms: HTTPS | Security algorithms: 802.1x RADIUS | SSH/SSL support: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Number of static routes: 32 | Firmware upgradeable: Yes | Copper ethernet cabling technology: 100BASE-TX | Storage temperature (T-T): -20 - 70 °C | Number of VLANs: 256 | Operating relative humidity (H-H): 0 - 90% | Weight: 3.46 kg | Switching capacity: 100 Gbit/s | Power consumption (typical): 41.1 W | Management protocols: SNMP v1/v2 | Jumbo frames support: Yes | Store-and-forward: Yes | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Number of multicast groups filtered: 512 | Broadcast storm control: Yes | Networking standards: IEEE 802.1v | Flow control support: Yes | Depth: 257 mm | Supported network protocols: IP | Multicast support: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903