



Ubiquiti Pro Max 24 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Modelis: USW-Pro-Max-24

Gamintojas: UBIQUITI

EAN: 810084692738

Prekės kodas: 365707

435.00€

Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Warnings: Make sure the ventilation of the equipment is not blocked. | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | AC input frequency: 50/60 Hz | Power consumption (max): 50 W | Power over Ethernet (PoE): No | Power supply included: Yes | Networking standards: IEEE 802.1x | Reset button: Yes | Rack mounting: Yes | Form factor: 1U | Operating relative humidity (H-H): 10 - 90% | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Display type: LCM | Weight: 4.3 kg | Power connector: AC/DC | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic switching RJ-45 Ethernet ports quantity: 24 | Width: 442.4 mm | Operating temperature (T-T): -5 - 40 °C | Jumbo frames support: Yes | DHCP features: DHCP snooping | VLAN support: Yes | IGMP snooping: Yes | Switching capacity: 112 Gbit/s | Depth: 325 mm | Product colour: Grey | DHCP features: DHCP relay | Power source: AC/DC | Height: 43.7 mm | Cables included: Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| LED indicators: Status | LED indicators: Network | LED indicators: Speed | 10G support: Yes | AC input voltage: 100 - 240 V | LED indicators: Link | Loop protection: Yes | Rack mount kit: Yes | Port mirroring: Yes | Sustainability certificates: Federal Communications Commission (FCC) | Switch layer: L3 | Rate limiting: Yes | Sustainability certificates: CE | Static route: Yes | SFP+ module slots quantity: 2 | Broadcast storm control: Yes | Flow control support: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Throughput: 56 Gbit/s | Stackable: Yes | Virtual LAN features: Voice VLAN | 2.5G Ethernet (copper) ports quantity: 8

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903