Ubiquiti UniFi USW-PRO-8-POE network switch Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U White

Modelis: USW-Pro-8-PoE

Gamintojas: UBIQUITI

EAN: 810084692691

Prekės kodas: 365709

293.99€

Certification: CE, FCC, IC | Product colour: White | VLAN support: Yes | Form factor: 1U | DHCP features: DHCP server | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 10BASE-TX | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-FX | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Housing material: Metal | Networking standards: IEEE 802.3at | Power over Ethernet (PoE) power per port: 60 W | Sustainability

compliance: Yes | Networking standards: IEEE 802.3af | Power source: AC/DC | Number of power supply units: 1 | Auto MDI/MDI-X: Yes | Width: 200 mm | Total Power over Ethernet (PoE) budget: 120 W | Operating temperature (T-T): -5 - 45 °C | Housing material: Plastic | Half duplex: Yes | Power over Ethernet (PoE): Yes | Power supply included: Yes | Full duplex: Yes | 10G support: Yes | Switching capacity: 56 Gbit/s | Weight: 2.1 kg | Manual: Yes | Jumbo frames support: Yes | Operating relative humidity (H-H): 10 - 90% | Height: 44 mm | LED indicators: Speed | Depth: 248 mm | Input current: 2 A | LED indicators: PoE | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: System | LED indicators: Activity | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Power over Ethernet 4PPoE (PoE++) ports quantity: 2 | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Power over Ethernet plus (PoE+) ports quantity: 6 | Switch layer: L2/L3 | Throughput: 28 Gbit/s | Switch type: Managed | Authentication: Port-based authentication | Auto-sensing: Yes | Link aggregation: Yes | Spanning tree protocol: Yes | Flow control support: Yes | Static route: Yes | Port mirroring: Yes | Authentication type: IEEE 802.1x, RADIUS | SFP+ module slots quantity: 2