



# Ubiquiti UniFi Pro 24-Port PoE Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Silver

Modelis: USW-Pro-24-POE

Gamintojas: UBIQUITI

EAN: 817882027649

Prekės kodas: 365719

## 666.99€

Certification: CE, FCC, IC | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | IPv4 routes: 64 | Throughput: 44000 Mpps | Number of power supply units: 1 | Rate limiting: Yes | IGMP snooping: Yes | Full duplex: Yes | Packet buffer memory: 2 MB | Port mirroring: Yes | MAC address table: 16000 entries | Switching capacity: 88 Gbit/s | Forwarding rate: 65.472 Mpps | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 16 | System event log: Yes | DHCP features: DHCP server | DHCP features: DHCP snooping | Switch layer: L2/L3 | Link aggregation: Yes | Power over Ethernet 4PPoE (PoE++) ports quantity: 8 | Broadcast storm control: Yes | Jumbo frames support: Yes | Warnings: Avoid

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

contact of the device with liquid. | Number of VLANs: 1000 | Switch type: Managed | 10G support: Yes | SFP+ module slots quantity: 2 | DHCP features: DHCP relay | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Static route: Yes | Power supply included: Yes | Authentication type: IEEE 802.1x, RADIUS | Flow control support: Yes | Height: 43.7 mm | Form factor: 1U | Reset button: Yes | Quality of Service (QoS) support: Yes | Product colour: Silver | AC input frequency: 50 - 60 Hz | AC input voltage: 100 - 240 V | LED indicators: Link | Power source: AC | Power consumption (max): 450 W | LED indicators: Speed | LED indicators: System | LED indicators: PoE | Power over Ethernet (PoE) power per port: 64 W | Web-based management: Yes | Networking standards: IEEE 802.3at | Operating relative humidity (H-H): 10 - 90% | Display type: LCM | LED indicators: Activity | Width: 442.4 mm | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -5 - 40 °C | VLAN support: Yes | Rack mounting: Yes | Total Power over Ethernet (PoE) budget: 400 W | Weight: 4.3 kg | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.3af | Redundant power supply (RPS) support: Yes | Depth: 285.4 mm

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903