



# Ubiquiti Pro Max 16 L3 2.5G Ethernet (100/1000/2500) 1U Grey



Modelis: USW-Pro-Max-16

Gamintojas: UBIQUITI

EAN: 810084694565

Prekės kodas: 365727

## 274.98€

Networking standards: IEEE 802.1x | Operating relative humidity (H-H): 10 - 90% | Weight: 1.95 kg | Product colour: Grey | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): No | Reset button: Yes | Operating temperature (T-T): -5 - 40 °C | Form factor: 1U | Input voltage: 4.8 - 5.2 V | LED indicators: Status | LED indicators: Network | LED indicators: Link | LED indicators: Speed | Input current: 5 A | Stackable: Yes | Depth: 160 mm | Height: 43.7 mm | Heat dissipation: 85.3 BTU/h | Access Control List (ACL): Yes | DHCP features: DHCP server | Switch layer: L3 | Cables included: Power | DHCP features: DHCP snooping | DHCP features: DHCP guarding | Link aggregation: Yes | Throughput: 42 Gbit/s | Jumbo frames support: Yes | Loop protection: Yes | Gigabit Ethernet (copper) ports quantity: 12 | Virtual LAN features: Voice VLAN | Rack mounting: Yes | DHCP features: DHCP relay | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Rate limiting: Yes | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Fanless: Yes | Display type: LCM | Authentication type: IEEE 802.1x | 10G support: Yes | Forwarding rate: 62 Mpps | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

VLANs: 1000 | Rack mount kit: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Switching capacity: 84 Gbit/s | Power consumption (max): 25 W | VLAN support: Yes | Flow control support: Yes | Broadcast storm control: Yes | Power supply included: Yes | Static route: Yes | IGMP snooping: Yes | Packet buffer memory: 1.5 MB | Power connector: AC/DC | Port mirroring: Yes | MAC address table: 16000 entries | Width: 325.1 mm | SFP+ module slots quantity: 2 | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: CE | 2.5G Ethernet (copper) ports quantity: 4 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | IPv4 routes: 512 | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid.

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903