Ubiquiti Pro Max 16 PoE Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Modelis: USW-Pro-Max-16-PoE

Gamintojas: UBIQUITI

EAN: 810084694572

Prekės kodas: 365728

385.99€

Cables included: Power | Operating temperature (T-T): -5 - 40 °C | Power consumption (max): 30 W | Reset button: Yes | Networking standards: IEEE 802.1x | Weight: 2.1 kg | AC input voltage: 100 - 240 V | AC input frequency: 50/60 Hz | LED indicators: System | Product colour: Grey | Power over Ethernet (PoE): Yes | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Switch layer: L3 | Manual: Yes | Operating relative humidity (H-H): 10 - 90% | DHCP features: DHCP snooping | Port mirroring: Yes | Housing material: Steel | DHCP features: DHCPv6 relay | Basic switching RJ-45 Ethernet ports quantity: 16 | Warnings: Make sure the ventilation of the equipment is not blocked. | Power over

Ethernet (PoE) power per port: 15 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Redundant power supply (RPS) support: Yes | Multicast support: Yes | Depth: 160 mm | IGMP snooping: Yes | 10G support: Yes | Power over Ethernet plus (PoE+) ports quantity: 12 | Power over Ethernet 4PPoE (PoE++) ports quantity: 4 | DC input voltage: 44 - 57 V | Rate limiting: Yes | Total Power over Ethernet (PoE) budget: 180 W | Height: 43.7 mm | Gigabit Ethernet (copper) ports quantity: 12 | Throughput: 42 Gbit/s | Jumbo frames support: Yes | Loop protection: Yes | Display type: LCM | Power supply included: Yes | Compliance certificates: Industry Canada (IC) | Switching capacity: 84 Gbit/s | Mounting brackets included: Yes | Compliance certificates: Federal Communications Commission (FCC) | Forwarding rate: 62.496 Mpps | Power connector: DC-in jack | Width: 325.1 mm | Rack mounting: Yes | Compliance certificates: CE | Switch type: Managed | Virtual LAN features: Voice VLAN | Flow control support: Yes | Power source: AC/DC | SFP+ module slots quantity: 2 | Broadcast storm control: Yes | 2.5G Ethernet (copper) ports quantity: 4