**SHOPRO**

# Ubiquiti USW-PRO-MAX-48-POE network switch L3 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) Grey

Modelis: USW-Pro-Max-48-PoE

Gamintojas: UBIQUITI

EAN: 810084692721

Prekės kodas: 365729

## 1,200.99€

Power connector: AC-in jack | Switching capacity: 224 Gbit/s | 10G support: No | Power supply included: Yes | Power over Ethernet (PoE) power per port: 15.4 W | Compliance certificates: National Defense Authorization Act (NDAA) | Power over Ethernet 4PPoE (PoE++) ports quantity: 16 | Compliance certificates: Industry Canada (IC) | Jumbo frames support: Yes | Compliance certificates: Federal Communications Commission (FCC) | 2.5G Ethernet (copper) ports quantity: 16 | Compliance certificates: CE | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) |

Warnings: Make sure the ventilation of the equipment is not blocked. | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Basic switching RJ-45 Ethernet ports quantity: 48 | Sustainability compliance: Yes | IPv4 routes: 12000 | Rate limiting: Yes | Gigabit Ethernet (copper) ports quantity: 32 | DHCP features: DHCP guarding | DHCP features: DHCP server | Heat dissipation: 341.2 BTU/h | Switch type: Managed | Loop protection: Yes | Broadcast storm control: Yes | Static route: Yes | Flow control support: Yes | DHCP features: DHCPv6 snooping | Switch layer: L3 | DHCP features: DHCP relay | Packet buffer memory: 2 MB | Port mirroring: Yes | MAC address table: 32000 entries | Power over Ethernet (PoE) type supported: PoE+ | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Number of VLANs: 1000 | Rack mount kit: Yes | Virtual LAN features: Voice VLAN | Backlight display: Yes | Power over Ethernet plus (PoE+) ports quantity: 32 | Throughput: 112 Gbit/s | IGMP snooping: Yes | Forwarding rate: 167 Mpps | Power over Ethernet (PoE) voltage: 57 V | SFP+ module slots quantity: 4 | Product colour: Grey | Form factor: 1U | LED indicators: System | Rack mounting: Yes | Reset button: Yes | AC input frequency: 50/60 Hz | Quality of Service (QoS) support: Yes | Operating relative humidity (H-H): 10 - 90% | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.1x | Height: 43.7 mm | Cables included: Power | Power over Ethernet (PoE): Yes | Display type: LCM | Manual: Yes | Operating temperature (T-T): -5 - 40 °C | Total Power over Ethernet (PoE) budget: 720 W | Power consumption (max): 820 W | Weight: 6.2 kg | Power source: AC | Width: 442.4 mm | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Depth: 399.6 mm