



ZyXel GS1100-10HP v2

Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: GS1100-10HP-EU0102F

Gamintojas: ZYXEL

EAN: 4718937621187

Prekės kodas: 365739

138.99€

Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | LED indicators: Yes | Power consumption (max): 156.1 W | Harmonized System (HS) code: 85176990 | Switch type: Unmanaged | Storage relative humidity (H-H): 10 - 95% | Auto MDI/MDI-X: Yes | Storage temperature (T-T): -40 - 70 °C | DC input voltage: 54 V | Package depth: 304 mm | Wall mountable: Yes | Networking standards: IEEE 802.3at | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 1000070 h | Package width: 228 mm | Depth: 104 mm | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3x | Total Power over Ethernet (PoE) budget: 130 W | Package height: 67 mm | Products per master (outer) case: 8 pc(s) | Networking standards: IEEE 802.3 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Master (outer) case length: 558 mm | Weight: 730 g | Forwarding rate: 14.88 Mpps | MAC address table: 8000 entries | Power source: AC/DC | Master (outer) case width: 323 mm | Master (outer) case gross weight: 13.7 kg | Width: 250 mm | Package weight: 1.97 kg | Power connector: DC-in jack | Heat dissipation: 89 BTU/h | Switching capacity: 20 Gbit/s | 10G support: No | Operating relative humidity (H-H): 10 - 90% | Basic switching RJ-45 Ethernet ports quantity: 8 | Ethernet LAN data rates: 100,1000 Mbit/s | Power over Ethernet (PoE): Yes | Product colour: Black | Power supply included: Yes | Networking standards: IEEE 802.3u | Operating temperature (T-T): 0 - 50 °C | Packet buffer memory: 0.256 MB | Height: 27 mm | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | AC input frequency: 50 - 60 Hz | Power over Ethernet (PoE) ports quantity: 8 | SFP module slots quantity: 2 | Jumbo frames: 9000 | Jumbo frames support: Yes | Master (outer) case height: 275 mm | Warnings: Do not use the device in damp conditions to avoid a short circuit. | Warnings: Do not open the housing of the unit due to the risk of electric shock. | Warnings: Electronic devices should be recycled in accordance with local regulations. | Sustainability certificates: RoHS | Sustainability compliance: Yes | Compliance certificates: RoHS