



Zyxel GS1900- 24E-EU0103F network switch Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Modelis: GS1900-24E-EU0103F

Gamintojas: ZYXEL

EAN: 4718937621132

Prekės kodas: 365749

108.98€

Certification: EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/ 48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant | Port mirroring: Yes | Power source: AC | Reset button: Yes | Forwarding rate: 35.7 Mpps | Virtual LAN features: Stacked VLAN | Stackable: Yes | Package width: 325 mm | AC input frequency: 50 - 60 Hz | Authentication type: RADIUS, TACACS+ | Package weight: 2.05 kg | Cables included: AC | Full duplex: Yes | Packet buffer memory: 0.525 MB | Wall mountable: Yes | Power over Ethernet (PoE): No | MAC address table: 8000 entries | Height: 42 mm | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1w | Heat dissipation: 51.49 BTU/h | Weight: 1.56 kg | Basic switching RJ-45 Ethernet ports type:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Gigabit Ethernet (10/100/1000) | LED indicators: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Mean time between failures (MTBF): 804.714 h | AC input voltage: 100 - 240 V | Depth: 162 mm | DHCP features: DHCP client | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Spanning tree protocol: Yes | Jumbo frames: 9000 | Package type: Box | Power consumption (max): 15.1 W | Power connector: AC-in jack | Networking standards: IEEE 802.3u | MAC address auto-learning supported: Yes | Virtual LAN features: VLAN mapping | Switch type: Managed | VLAN support: Yes | Product colour: Black | Link aggregation: Yes | Storage relative humidity (H-H): 10 - 95% | Password protection: Yes | System event log: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Jumbo frames support: Yes | Rack mounting: Yes | Networking standards: IEEE 802.1D | Form factor: 1U | Switch layer: L2 | Store-and-forward: Yes | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Rack mount kit: Yes | Package height: 71 mm | Static port security: Yes | SSH/SSL support: Yes | IGMP snooping: Yes | Switching capacity: 48 Gbit/s | Basic switching RJ-45 Ethernet ports quantity: 24 | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.3x | MIB support: RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215 generic traps, RFC 1493 bridge, Zyxel private common MIB | Ethernet LAN data rates: 10,100,1000 Mbit/s | Width: 267 mm | Flow control support: Yes | Package depth: 223 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903