



Zyxel GS-1900-24 v2 Managed L2 Gigabit Ethernet (10/100/1000) 1U Black



Modelis: GS1900-24-EU0102F

Gamintojas: ZYXEL

EAN: 4718937621231

Prekės kodas: 365750

145.99€

Certification: EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/ 48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant | DHCP features: DHCP client | Depth: 131 mm | Form factor: 1U | Package width: 561 mm | Rack mounting: Yes | Switch layer: L2 | Reset button: Yes | Full duplex: Yes | Cables included: AC | System event log: Yes | Virtual LAN features: Voice VLAN | Stackable: Yes | Port mirroring: Yes | Weight: 2.09 kg | Power connector: AC-in jack | Forwarding rate: 39 Mpps | Switching capacity: 52 Gbit/s | Power source: AC | Spanning tree protocol: Yes | Jumbo frames: 9000 | Packet buffer memory: 0.525 MB | Package weight: 2.85 kg | Height: 44 mm | Virtual LAN features: VLAN Identifier (VLAN ID) | Harmonized System (HS) code: 85176990 | SFP module slots quantity: 2 | Static port security: Yes | Power over Ethernet (PoE): No | Width: 440 mm | Link aggregation: Yes | Operating temperature (T-T): 0 - 50 °C |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Authentication type: RADIUS, TACACS+ | MAC address table: 8000 entries | Power consumption (max): 16 W | IGMP snooping: Yes | MAC address auto-learning supported: Yes | Password protection: Yes | VLAN support: Yes | Virtual LAN features: Tagged VLAN | Store-and-forward: Yes | Jumbo frames support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Rack mount kit: Yes | Package type: Box | LED indicators: Yes | Mean time between failures (MTBF): 432.673 h | 10G support: No | Package depth: 217 mm | Switch type: Managed | Package height: 82 mm | SSH/SSL support: Yes | Flow control support: Yes | MIB support: RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493 | Heat dissipation: 55 BTU/h | Basic switching RJ-45 Ethernet ports quantity: 24 | Storage relative humidity (H-H): 10 - 95% | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | AC input frequency: 50 - 60 Hz | Security algorithms: 802.1x RADIUS | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.1s | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Product colour: Black

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903