



Zyxel GS1915-8EP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Modelis: GS1915-8EP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937621934

Prekės kodas: 365755

139.98€

Certification: CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438 | Multicast support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Packet buffer memory: 0.525 MB | Electromagnetic compatibility: LVD EN60950-1, BSMI CNS14336-1 | Operating relative humidity (H-H): 10 - 95% | Number of VLANs: 8 | Power over Ethernet (PoE) ports quantity: 8 | MAC address table: 8000 entries | Manual: Yes | Depth: 104 mm | Forwarding rate: 11.9 Mpps | Power source: AC | Auto MDI/MDI-X: Yes | Switch layer: L2 | Flow control support: Yes | Power connector: AC-in jack | System event log: Yes | Power consumption (max): 72 W | 10G support: No | Total Power over Ethernet (PoE) budget: 60 W | Rate limiting: Yes | Package depth: 227 mm | Package width: 302 mm | Basic switching RJ-45 Ethernet ports quantity: 8 | Full duplex: Yes | Switching capacity: 16 Gbit/s |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

User guide: Yes | SSH/SSL support: Yes | Management protocols: SNMP v1,v2,v3, RMON (1,2,3,9) | Height: 27 mm | Jumbo frames: 9000 | Broadcast storm control: Yes | Heat dissipation: 245.52 BTU/h | Gigabit Ethernet (copper) ports quantity: 8 | Switch type: Managed | Mean time between failures (MTBF): 1641000 h | Copper ethernet cabling technology: 10BASE-T | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-T | Package height: 64 mm | Cables included: AC | Jumbo frames support: Yes | Copper ethernet cabling technology: 100BASE-TX | Power over Ethernet (PoE): Yes | Harmonized System (HS) code: 85176990 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 10 - 95% | Width: 250 mm | IGMP snooping: Yes | MIB support: RFC 1213 MIB II, RFC 2819, RFC 1215, RFC 1493 | Package weight: 1.4 kg | Operating temperature (T-T): 0 - 40 °C | Weight: 620 g | Quick start guide: Yes | AC input voltage: 200 - 240 V | LED indicators: Yes | Product colour: Black | AC input frequency: 50 - 60 Hz | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3ad