



Zyxel XMG1915-10EP Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE)

Modelis: XMG1915-10EP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937631452

Prekės kodas: 365756

308.99€

DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | 10G support: Yes | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Total Power over Ethernet (PoE) budget: 130 W | Internal memory: 256 MB | VLAN support: Yes | Flash memory: 32 MB | Height: 27 mm | Firmware upgradeable: Yes | Mean time between failures (MTBF): 394.499 h | AC input voltage: 100 - 240 V | Power source: AC/PoE | Basic switching RJ-45 Ethernet ports quantity: 8 | Packet buffer memory: 1.5 MB | Weight: 780 g | LED indicators: Yes | Switching capacity: 80 Gbit/s | MAC address table: 16000 entries | Power consumption (max): 150 W | Operating relative humidity (H-H): 5 - 95% | Cables included: AC | Jumbo frames support: Yes | Networking standards: IEEE 802.3bt | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.3bz | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3x | MAC address filtering: Yes | Security algorithms: SNMPv3 | Security algorithms: SNMP | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Depth: 104 mm | Rack mounting: Yes | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Networking standards: IEEE 802.3az | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | AC input frequency: 50/60 Hz | Power supply included: Yes | Power over Ethernet (PoE) ports quantity: 8 | Width: 250 mm | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Storage relative humidity (H-H): 5 - 95% | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Forwarding rate: 59.5 Mpps | SSH/SSL support: Yes | Jumbo frames: 12000 | SFP+ module slots quantity: 2 | Switch type: Managed | Authentication type: RADIUS | Virtual LAN features: Port-based VLAN | Virtual LAN features: Voice VLAN | Multicast support: Yes | Virtual LAN features: MAC address-based VLAN | Switch layer: L2 | Multicast features: Multicast forwarding | IGMP snooping: Yes