



**ZyXel GS1350-
12HP-EU0101F
network switch
Managed L2
Gigabit Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**

Modelis: GS1350-12HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937604388

Prekės kodas: 365758

244.99€

Firmware upgradeable: Yes | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 5 - 95% | Multicast support: Yes | Depth: 162 mm | Virtual LAN features: MAC address-based VLAN | Total Power over Ethernet (PoE) budget: 130 W | Virtual LAN features: Port-based VLAN | DHCP features: DHCP client | DHCP features: DHCP relay | SFP module slots quantity: 2 | Operating temperature (T-T): -20 - 50 °C | DHCP features: DHCP snooping | Switch layer: L2 | AC input voltage: 100 - 240 V | LED indicators: Yes | Heat dissipation: 546.62 BTU/h | Switch type: Managed | Mean

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

time between failures (MTBF): 1065025.45 h | Loop protection: Yes | Height: 44 mm | Cables included: AC | Noise level: 27.3 dB | Power over Ethernet (PoE): Yes | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | Broadcast storm control: Yes | Spanning tree protocol: Yes | System event log: Yes | IGMP snooping: Yes | IGMP proxy: Yes | Width: 267 mm | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Web-based management: Yes | MAC address filtering: Yes | Weight: 1.63 kg | Power consumption (max): 160.3 W | Networking standards: IEEE 802.3at | Port mirroring: Yes | Switching capacity: 24 Gbit/s | Power over Ethernet (PoE) ports quantity: 8 | Security algorithms: SSH | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Packet buffer memory: 0.525 MB | Fiber ethernet cabling technology: 1000BASE-X | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1w | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-T | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Forwarding rate: 17.8 Mpps | Basic switching RJ-45 Ethernet ports quantity: 10 | Configuring Location Settings (CLI): Yes | MAC address table: 8000 entries | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Product colour: Grey | Queue scheduling algorithms: WFQ | Rack mount kit: Yes | Storage temperature (T-T): -40 - 70 °C | 10G support: No | Number of VLANs: 256 | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3ad | Security algorithms: SNMP | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903