



Zyxel GS1920-24V2 Managed Gigabit Ethernet (10/100/1000) Black



Modelis: GS1920-24V2-EU0101F

Gamintojas: ZYXEL

EAN: 4718937601851

Prekės kodas: 365761

227.99€

Certification: RoHS | Width: 441 mm | LED indicators: Yes | Access Control List (ACL): Yes | CPU defense: Yes | Height: 44 mm | Heat dissipation: 76.73 BTU/h | Switch type: Managed | Rack mounting: Yes | Virtual LAN features: Protocol-based VLAN | Rate limiting: Yes | Combo SFP ports quantity: 4 | Safety: LVD, BSMI | Package weight: 2.91 kg | Cables included: AC | Mean time between failures (MTBF): 911301 h | Power over Ethernet (PoE): No | AC input voltage: 100 - 240 V | System event log: Yes | ARP inspection: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | IGMP snooping: Yes | IP-MAC-Port binding: Yes | MAC address table: 16000 entries | Multicast support: Yes | Virtual LAN features: Voice VLAN | Virtual LAN features: Private VLAN | Depth: 131 mm | Internal memory: 256 MB | 10G support: No | DHCP features: DHCPv6 relay | Package depth: 214 mm | Harmonized System (HS) code: 85176990 | Fiber optic connector: SFP | Operating temperature (T-T): 0 - 50 °C | Spanning tree protocol: Yes | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Port-based VLAN | Virtual LAN features: IP

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

subnet-based VLAN | Package width: 558 mm | Packet buffer memory: 1.5 MB | Power consumption (max): 22.5 W | Weight: 2.1 kg | Fiber ethernet cabling technology: 1000BASE-X | Forwarding rate: 42 Mpps | Switching capacity: 56 Gbit/s | Electromagnetic compatibility: FCC 15 A, CE A, BSMI EMC | Operating relative humidity (H-H): 10 - 95% | AC input frequency: 50 - 60 Hz | Authentication type: IEEE 802.1x, RADIUS | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes | Networking standards: IEEE 802.3ad | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.1x | Queue scheduling algorithms: WFQ | Product colour: Black | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Authentication: Guest VLAN, Port-based authentication | Rack mount kit: Yes | Storage relative humidity (H-H): 10 - 95% | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Basic switching RJ-45 Ethernet ports quantity: 24 | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Password protection: Yes | Package height: 79 mm | Copper ethernet cabling technology: 100BASE-TX

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903