



# Zyxel GS1920-24HPV2 Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Modelis: GS192024HPV2-EU0101F

Gamintojas: ZYXEL

EAN: 4718937601936

Prekės kodas: 365762

## 327.99€

Certification: RoHS | Product colour: Black | MAC address filtering: Yes | AC input frequency: 50 - 60 Hz | LED indicators: Yes | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Weight: 3.8 kg | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1w | Security algorithms: 802.1x RADIUS | Networking standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

IEEE 802.3at | Virtual LAN features: Port-based VLAN | Cables included: AC | DHCP features: DHCP client | DHCP features: DHCP relay | System event log: Yes | Virtual LAN features: IP subnet-based VLAN | Total Power over Ethernet (PoE) budget: 375 W | Virtual LAN features: MAC address-based VLAN | Multicast support: Yes | Depth: 270 mm | Virtual LAN features: Voice VLAN | DHCP features: DHCP snooping | Height: 44 mm | DHCP features: DHCPv6 relay | Package weight: 4.97 kg | Virtual LAN features: Protocol-based VLAN | Operating temperature (T-T): 0 - 50 °C | Virtual LAN features: Private VLAN | Fiber ethernet cabling technology: 1000BASE-X | Operating relative humidity (H-H): 10 - 95% | Electromagnetic compatibility: FCC 15 A, CE A, BSMI EMC | MAC address table: 16000 entries | Noise level: 27.2 dB | IP-MAC-Port binding: Yes | Fiber optic connector: SFP | Combo SFP ports quantity: 4 | Safety: LVD, BSMI | ARP inspection: Yes | Power over Ethernet (PoE): Yes | Width: 441 mm | Package width: 616 mm | Rack mounting: Yes | Authentication type: IEEE 802.1x, RADIUS | IGMP snooping: Yes | CPU defense: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 10 - 95% | Power over Ethernet (PoE) ports quantity: 24 | Heat dissipation: 1580.54 BTU/h | Packet buffer memory: 1.5 MB | Spanning tree protocol: Yes | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Switch type: Managed | Package height: 107 mm | VLAN support: Yes | Switching capacity: 56 Gbit/s | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Rate limiting: Yes | Password protection: Yes | Mean time between failures (MTBF): 638691 h | Access Control List (ACL): Yes | Queue scheduling algorithms: WFQ | Authentication: Guest VLAN, Port-based authentication | Rack mount kit: Yes | Internal memory: 256 MB | Package depth: 355 mm | Power consumption (max): 463.5 W | Forwarding rate: 42 Mpps | Copper ethernet cabling technology: 100BASE-TX | Harmonized System (HS) code: 85176990 | Basic switching RJ-45 Ethernet ports quantity: 24 | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR)

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903