



ZyXel GS1920-48V2 Managed Gigabit Ethernet (10/100/1000) Black



Modelis: GS1920-48V2-EU0101F

Gamintojas: ZYXEL

EAN: 4718937601899

Prekės kodas: 365763

379.99€

Certification: RoHS | Noise level: 26 dB | Product colour: Black | AC input frequency: 50 - 60 Hz | Package width: 496 mm | Power over Ethernet (PoE): No | AC input voltage: 100 - 240 V | Width: 440 mm | Operating relative humidity (H-H): 10 - 95% | Packet buffer memory: 1.5 MB | LED indicators: Yes | Harmonized System (HS) code: 85176990 | Power consumption (max): 36.9 W | Operating temperature (T-T): 0 - 50 °C | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Rack mounting: Yes | Switching capacity: 100 Gbit/s | Package height: 90 mm | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 44 | VLAN support: Yes | Weight: 2.8 kg | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | MAC address table: 16000 entries | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1ab | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Networking standards: IEEE 802.1w | Depth: 220 mm | Internal memory: 256 MB | Fiber optic connector: SFP | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 10 - 95% | Warnings: Follow the safety guidelines for electrical current. | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Password protection: Yes | SFP module slots quantity: 2 | Package weight: 3.97 kg | Height: 44.5 mm | Mean time between failures (MTBF): 672235 h | 10G support: No | Safety: LVD, BSMI | Package depth: 289 mm | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Cables included: AC | Forwarding rate: 74 Mpps | IP-MAC-Port binding: Yes | System event log: Yes | Fiber ethernet cabling technology: 1000BASE-X | DHCP features: DHCP snooping | Rate limiting: Yes | DHCP features: DHCPv6 relay | DHCP features: DHCP client | DHCP features: DHCP relay | Virtual LAN features: Port-based VLAN | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Voice VLAN | Virtual LAN features: Protocol-based VLAN | Multicast support: Yes | Virtual LAN features: IP subnet-based VLAN | Switch type: Managed | Access Control List (ACL): Yes | Heat dissipation: 125.83 BTU/h | Spanning tree protocol: Yes | Combo SFP ports quantity: 4 | Virtual LAN features: Private VLAN | CPU defense: Yes | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | ARP inspection: Yes | Queue scheduling algorithms: WFQ | IGMP snooping: Yes | Electromagnetic compatibility: FCC 15 A, CE A, BSMI EMC | Authentication: Guest VLAN, Port-based authentication | Rack mount kit: Yes | Authentication type: IEEE 802.1x, RADIUS