



**ZyXel XS1930-
12HP-ZZ0101F
network switch
Managed L3 10G
Ethernet
(100/1000/10000)
Power over
Ethernet (PoE)
Black**

Modelis: XS1930-12HP-ZZ0101F

Gamintojas: ZYXEL

EAN: 4718937605262

Prekės kodas: 365765

660.99€

Networking standards: IEEE 802.3an | Web-based management: Yes | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.3ae | Warnings: Follow the safety guidelines for electrical current. | Product colour: Black | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3bt | Warnings: Make sure the ventilation of the equipment is not blocked. | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3x | Networking standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

IEEE 802.3at | Warnings: Avoid contact of the device with liquid. | Networking standards: IEEE 802.1w | Ethernet LAN data rates: 100,1000,2500,5000,10000 Mbit/s | AC input frequency: 50 - 60 Hz | AC input voltage: 100 - 240 V | Weight: 2.8 kg | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | LED indicators: Yes | Operating temperature (T-T): -20 - 50 °C | 10G support: Yes | Port mirroring: Yes | Cloud-managed: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Configuring Location Settings (CLI): Yes | VLAN support: Yes | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | SFP+ module slots quantity: 2 | Switching capacity: 240 Gbit/s | Multicast support: Yes | Total Power over Ethernet (PoE) budget: 375 W | Switch type: Managed | Power over Ethernet plus (PoE+) ports quantity: 8 | MAC address table: 16000 entries | Power consumption (max): 493 W | Operating relative humidity (H-H): 5 - 95% | Width: 330 mm | Heat dissipation: 151.06 BTU/h | Harmonized System (HS) code: 85176990 | Rack mounting: Yes | Power supply included: Yes | Quality of Service (QoS) support: Yes | Storage relative humidity (H-H): 5 - 95% | MIB support: Y | Depth: 230 mm | Switch layer: L3 | Height: 44 mm