



Zyxel GS2220-10-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Black

Modelis: GS2220-10-EU0101F

Gamintojas: ZYXEL

EAN: 4718937607365

Prekės kodas: 365767

194.99€

Certification: LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A | Power consumption (max): 11 W | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 1213492 h | Access Control List (ACL): Yes | Switch type: Managed | Height: 44 mm | Package weight: 2.21 kg | Cables included: AC | Rack mounting: Yes | Virtual LAN features: Voice VLAN | Heat dissipation: 37.51 BTU/h | DHCP features: DHCP client | DHCP features: DHCP relay | Multicast support: Yes | DHCP features: DHCPv6 client | AC input frequency: 50 - 60 Hz | Harmonized System (HS) code: 85176990 | System event log: Yes | DHCP features: DHCP snooping | Switch layer: L2 | DHCP features: DHCPv6 relay | Packet buffer memory: 1.5 MB | Virtual LAN features: Protocol-based VLAN | Authentication type: IEEE 802.1x, RADIUS | Virtual LAN features: Private VLAN | Virtual LAN features: Port-based VLAN | Width:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

267 mm | Package width: 375 mm | Power over Ethernet (PoE): No | IGMP snooping: Yes | Operating relative humidity (H-H): 10 - 95% | MAC address table: 16000 entries | Weight: 1.3 kg | Forwarding rate: 15 Mpps | Switching capacity: 20 Gbit/s | Depth: 162 mm | Link aggregation: Yes | Spanning tree protocol: Yes | Broadcast storm control: Yes | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 10 | Configuring Location Settings (CLI): Yes | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Package height: 61 mm | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fanless: Yes | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Rate limiting: Yes | Firmware upgradeable: Yes | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Security algorithms: SNMPv2 | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 10 - 95% | Authentication: Guest VLAN, MAC-based authentication | 10G support: No | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | Networking standards: IEEE 802.3az | Product colour: Black | Package depth: 235 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Internal memory: 256 MB | Flow control support: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903