



ZyXel GS2220-10HP-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Modelis: GS2220-10HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937607402

Prekės kodas: 365768

353.99€

Certification: LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A | Noise level: 41 dB | Packet buffer memory: 1.5 MB | Product colour: Black | Mean time between failures (MTBF): 587477 h | Heat dissipation: 718.828 BTU/h | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 10 - 95% | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | AC input voltage: 100 - 240 V | DHCP features: DHCP client | DHCP features: DHCP relay | Power over Ethernet (PoE): Yes | DHCP features: DHCP snooping | Switch layer: L2 | Firmware upgradeable: Yes | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

consumption (max): 210.8 W | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Cables included: AC | Access Control List (ACL): Yes | Switch type: Managed | Height: 44 mm | Rack mounting: Yes | Total Power over Ethernet (PoE) budget: 180 W | Operating temperature (T-T): 0 - 50 °C | Package width: 375 mm | Package weight: 2.7 kg | IGMP snooping: Yes | MAC address table: 16000 entries | Multicast support: Yes | DHCP features: DHCPv6 client | Package depth: 235 mm | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Copper ethernet cabling technology: 10BASE-TX | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | Internal memory: 256 MB | Package height: 61 mm | Warnings: Avoid contact of the device with liquid. | 10G support: No | Web-based management: Yes | MAC address filtering: Yes | DHCP features: DHCPv6 relay | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Harmonized System (HS) code: 85176990 | Flow control support: Yes | Depth: 162 mm | Weight: 1.8 kg | Width: 267 mm | Switching capacity: 20 Gbit/s | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 10 - 95% | Power over Ethernet (PoE) ports quantity: 8 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Basic switching RJ-45 Ethernet ports quantity: 10 | Warnings: Make sure the ventilation of the equipment is not blocked. | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Authentication type: IEEE 802.1x, RADIUS | Authentication: Guest VLAN, MAC-based authentication | Link aggregation: Yes | System event log: Yes | Spanning tree protocol: Yes | Forwarding rate: 15 Mpps | Broadcast storm control: Yes | Virtual LAN features: Private VLAN | Rate limiting: Yes | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Port-based VLAN | Virtual LAN features: Voice VLAN | Combo SFP ports quantity: 2 | Configuring Location Settings (CLI): Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903