



Zyxel GS2220-28HP-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: GS2220-28HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937607488

Prekės kodas: 365770

454.98€

Certification: LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A | Weight: 3.8 kg | Product colour: Black | Package weight: 4.97 kg | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | AC input frequency: 50 - 60 Hz | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

IEEE 802.3ab | Networking standards: IEEE 802.1p | Package width: 616 mm | Operating relative humidity (H-H): 10 - 95% | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Firmware upgradeable: Yes | Operating temperature (T-T): 0 - 50 °C | Power over Ethernet (PoE): Yes | Width: 441 mm | Storage relative humidity (H-H): 10 - 95% | Noise level: 49.8 dB | Cables included: AC | Web-based management: Yes | MAC address filtering: Yes | Package depth: 355 mm | Power consumption (max): 463.5 W | Warnings: Avoid contact of the device with liquid. | Package height: 107 mm | Warnings: Follow the safety guidelines for electrical current. | AC input voltage: 100 - 240 V | Warnings: Make sure the ventilation of the equipment is not blocked. | Multicast support: Yes | Virtual LAN features: Port-based VLAN | Rate limiting: Yes | Switching capacity: 56 Gbit/s | Height: 44 mm | 10G support: No | System event log: Yes | Virtual LAN features: Private VLAN | Virtual LAN features: Protocol-based VLAN | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCPv6 client | DHCP features: DHCPv6 relay | Depth: 270 mm | Virtual LAN features: Voice VLAN | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Total Power over Ethernet (PoE) budget: 375 W | Flow control support: Yes | Authentication: Guest VLAN, MAC-based authentication | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | Broadcast storm control: Yes | Spanning tree protocol: Yes | Link aggregation: Yes | Copper ethernet cabling technology: 10BASE-TX | Flash memory: 32 MB | Copper ethernet cabling technology: 1000BASE-T | Basic switching RJ-45 Ethernet ports quantity: 24 | Authentication type: IEEE 802.1x, RADIUS | Power over Ethernet (PoE) ports quantity: 24 | DHCP features: DHCP snooping | Switch layer: L2 | VLAN support: Yes | MAC address table: 16000 entries | IGMP snooping: Yes | Packet buffer memory: 1.5 MB | Internal memory: 256 MB | Access Control List (ACL): Yes | Combo SFP ports quantity: 4 | Configuring Location Settings (CLI): Yes | Forwarding rate: 42 Mpps | Mean time between failures (MTBF): 693245 h | Heat dissipation: 1580.535 BTU/h | Switch type: Managed

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903