



Zyxel XGS2220-30HP Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: XGS2220-30HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937625055

Prekės kodas: 365772

649.00€

Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Power over Ethernet (PoE) ports quantity: 26 | Basic switching RJ-45 Ethernet ports quantity: 24 | Flash memory: 64 MB | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | LED indicators: Yes | Product colour: Black | Operating temperature (T-T): -20 - 50 °C | AC input frequency: 50 - 60 Hz | DHCP features: DHCP relay | DHCP features: DHCP server | Package depth: 503 mm | Internal memory: 1024 MB | Jumbo frames support: Yes | Total Power over Ethernet (PoE) budget: 400 W | Package height: 95 mm | Depth: 330 mm | 10G support: Yes | Multicast support: Yes | Package width: 580 mm | Power consumption (max): 477 W | Height: 44 mm | Package weight: 5.77 kg |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power over Ethernet (PoE): Yes | Width: 441 mm | IGMP snooping: Yes | MAC address table: 32000 entries | Weight: 4.35 kg | Switching capacity: 168 Gbit/s | AC input voltage: 100 - 240 V | Mean time between failures (MTBF): 268.305 h | Rack mounting: Yes | Packet buffer memory: 2 MB | Security algorithms: SNMP | Networking standards: IEEE 802.1x | Security algorithms: SNMPv3 | Storage relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3bt | Web-based management: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Networking standards: IEEE 802.3an | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3az | Power source: AC | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3ae | Switch layer: L3 | Routing entries: 64 | Switch type: Managed | Heat dissipation: 1626.57 BTU/h | Installed SFP+ modules quantity: 4 | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Make sure the ventilation of the equipment is not blocked. | 10G Ethernet (copper) ports quantity: 2 | Multicast Listener Discovery (MLD) snooping: MLD v1/v2 | Static route: Yes | Authentication type: IEEE 802.1x, RADIUS, TACACS+ | IGMP proxy: Yes | Cloud-managed: Yes | BPDU filtering/protection: Yes | Forwarding rate: 125 Mpps | GARP VLAN Registration Protocol (GVRP): Yes | ARP inspection: Yes