

Zyxel GS1900-10HP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: ZYXEL · Modelis: GS1900-10HP-EU0102F · EAN: 4718937621200 · Prekės kodas: 365774



137,90 €

Kaina su PVM

Be PVM: 113,97 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management SNMP, RMON, ICMP, Syslog
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8 Console port: RJ-45
- ✓ 10BASE-T, 100BASE-T, 1000BASE-T
- ✓ MAC address table: 8000 entries Switching capacity: 20 Gbit/s
- ✓ AC Power supply included Power over Ethernet (PoE)



Aprašymas

Near silent operation

The GS1900 Series includes both fan-less and built-in smart fan models. The smart fan is designed to automatically adjust speed based on device temperature. You can barely hear the sound while the switch is operating. It is ideal for your office environment.

Intelligent PoE+ powers more devices

PoE models (8HP/10HP/24EP/24HPv2/48HPv2) come with default PoE consumption mode which delivers only the actual power required by your networked devices, reserves the rest and optimizes its power budget. That means a single switch can power more APs, IP cameras and VoIP phones, ensuring a better ROI for your business. All of them support the IEEE 802.3at providing a maximum of 30W per port.

Speedy Gigabit performance—built for SMBs

The GS1900 is a series of switches with full non-blocking bandwidth of up to 1 Gbps per port. An ideal upgrade from an unmanaged switch, it's a

great choice for SMBs that want to enjoy high-speed business network applications at full wired non-blocking speed.

Techninė specifikacija

Specifications	
Sandėlio grupė	Enterprise and server products > KVM > Switches > Managed [+0][-0]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
System event log	Yes
MIB support	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215 generic traps, RFC 1493 bridge
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2
Console port	RJ-45
Network	
Networking standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
VLAN support	Yes
Virtual LAN features	Voice VLAN
Data transmission	
MAC address table	8000 entries
Switching capacity	20 Gbit/s
Throughput	14.88 Mpps
Jumbo frames	9000
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Security algorithms	802.1x RADIUS, SSL/TLS
MAC address filtering	Yes

Protocols

Management protocols	SNMP, RMON, ICMP, Syslog
----------------------	--------------------------

Design

Rack mounting	No
Product colour	Black
LED indicators	Yes
Wall mountable	Yes

Performance

Mean time between failures (MTBF)	800259 h
-----------------------------------	----------

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	95.3 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Total Power over Ethernet (PoE) budget	77 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%

Weight & dimensions

Width	250 mm
Depth	104 mm
Height	27 mm
Weight	720 g

Packaging content

Cables included	AC
-----------------	----

Certificates

Certification	CE, FCC, RCM, Class A, BSMI CNS 13438, LVD EN 62368-1, BSMI CNS 14336-1
---------------	---

Matmenys ir svoris

Matmenys (l × p × A)	7,00cm × 31,00cm × 23,00cm
Svoris	1,50kg