



Zyxel GS1900-10HP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: GS1900-10HP-EU0102F

Gamintojas: ZYXEL

EAN: 4718937621200

Prekės kodas: 365774

140.99€

Certification: CE, FCC, RCM, Class A, BSMI CNS 13438, LVD EN 62368-1, BSMI CNS 14336-1 | Depth: 104 mm | Switching capacity: 20 Gbit/s | Power consumption (max): 95.3 W | MAC address table: 8000 entries | Console port: RJ-45 | Quality of Service (QoS) support: Yes | Jumbo frames: 9000 | Throughput: 14.88 Mpps | Basic switching RJ-45 Ethernet ports quantity: 8 | SFP module slots quantity: 2 | Cables included: AC | Management protocols: SNMP, RMON, ICMP, Syslog | Rack mounting: No | Copper ethernet cabling technology: 1000BASE-T | Mean time between failures (MTBF): 800259 h | Height: 27 mm | Power source: AC | VLAN support: Yes | Power over Ethernet (PoE) ports quantity: 8 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

technology: 100BASE-T | Width: 250 mm | IGMP snooping: Yes | Switch type: Managed | System event log: Yes | Total Power over Ethernet (PoE) budget: 77 W | Wall mountable: Yes | Switch layer: L2 | 10G support: No | Virtual LAN features: Voice VLAN | DHCP features: DHCP client | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Storage relative humidity (H-H): 10 - 95% | MIB support: RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215 generic traps, RFC 1493 bridge | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Operating temperature (T-T): 0 - 40 °C | Product colour: Black | LED indicators: Yes | AC input voltage: 100 - 240 V | Weight: 720 g | AC input frequency: 50 - 60 Hz | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Networking standards: IEEE 802.3at | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1D | Security algorithms: SSL/TLS | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1w