



# Zyxel GS1350-6HP-EU0101F network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Modelis: GS1350-6HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937604487

Prekės kodas: 365775

---

## 162.99€

---

Queue scheduling algorithms: WFQ | Product colour: Grey | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | LED indicators: Yes | Mean time between failures (MTBF): 2021885.87 h | Loop protection: Yes | Virtual LAN features: MAC address-based VLAN | Switch type: Managed | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-T | Configuring Location Settings (CLI): Yes | Copper ethernet cabling technology: 10BASE-T | Total Power over Ethernet (PoE) budget: 60 W | Copper ethernet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

cabling technology: 100BASE-TX | DC input voltage: 52 - 57 V | Operating temperature (T-T): -20 - 50 °C | Virtual LAN features: Port-based VLAN | Operating relative humidity (H-H): 5 - 95% | Firmware upgradeable: Yes | Rate limiting: Yes | Security algorithms: SSH | Fiber ethernet cabling technology: 1000BASE-X | System event log: Yes | Harmonized System (HS) code: 85176990 | Web-based management: Yes | MAC address filtering: Yes | Switch layer: L2 | Networking standards: IEEE 802.1w | Broadcast storm control: Yes | Power consumption (max): 72 W | Power over Ethernet (PoE): Yes | Switching capacity: 12 Gbit/s | Width: 193 mm | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Networking standards: IEEE 802.3ad | Security algorithms: SNMP | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Spanning tree protocol: Yes | Storage temperature (T-T): -40 - 70 °C | Networking standards: IEEE 802.3at | Weight: 410 g | Networking standards: IEEE 802.3bt | Forwarding rate: 8.9 Mpps | Power over Ethernet (PoE) ports quantity: 5 | Power supply included: Yes | IGMP proxy: Yes | Depth: 84 mm | Height: 26 mm | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | DHCP features: DHCP snooping | IGMP snooping: Yes | SFP module slots quantity: 1 | Basic switching RJ-45 Ethernet ports quantity: 5 | DHCP features: DHCP client | DHCP features: DHCP relay | Multicast support: Yes | Heat dissipation: 245.52 BTU/h | 10G support: No | Number of VLANs: 256 | Packet buffer memory: 0.525 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Wall mountable: Yes | Port mirroring: Yes | MAC address table: 8000 entries

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903