



**Zyxel XGS1935-
28-EU0101F
network switch
Managed L2+/L3
Gigabit Ethernet
(10/100/1000)
1U Black**

Modelis: XGS1935-28-EU0101F

Gamintojas: ZYXEL

EAN: 4718937636297

Prekės kodas: 365778

239.99€

Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | LED indicators: Yes | Power consumption (typical): 11.5 W | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3x | Weight: 3.1 kg | Web-based management: Yes | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Switching capacity: 128 Gbit/s | Height: 433 mm | Product colour: Black | Power consumption (max): 23.2 W | Basic switching RJ-45 Ethernet ports quantity: 24 | Networking standards: IEEE 802.1w |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | Power source: AC | DHCP features: DHCP client | DHCP features: DHCP relay | Operating temperature (T-T): -20 - 50 °C | Depth: 270 mm | Form factor: 1U | Cables included: AC | Rack mounting: Yes | Warnings: Avoid contact of the device with liquid. | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Package height: 90 mm | Power over Ethernet (PoE): No | Width: 440 mm | Flash memory: 32 MB | Warnings: Make sure the ventilation of the equipment is not blocked. | Package width: 508 mm | Packet buffer memory: 1.5 MB | Internal memory: 512 MB | IGMP snooping: Yes | Package depth: 394 mm | 10G support: Yes | AC input voltage: 100 - 240 V | MAC address table: 16000 entries | Memory type: RAM / Flash | Package weight: 4.58 kg | Jumbo frames support: Yes | Power supply included: Yes | Forwarding rate: 95.2 Mpps | Cloud-managed: Yes | System event log: Yes | Switch layer: L2+/L3 | ARP inspection: Yes | Traffic shaping: Yes | Switch type: Managed | SFP+ module slots quantity: 4 | Configuring Location Settings (CLI): Yes | Rack mount kit: Yes | Jumbo frames: 9000 | Multicast support: Yes | Traffic classification: Yes | Stackable: Yes