

Zyxel XGS1935-28-EU0101F network switch Managed L2+/L3 Gigabit Ethernet (10/100/1000) 1U Black

Gamintojas: **ZYXEL** · Modelis: **XGS1935-28-EU0101F** · EAN: **4718937636297** · Prekės kodas: **365778**



239,89 €

Kaina su PVM

Be PVM: **198,26 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2+/L3 Web-based management
- ✓ Quality of Service (QoS) support Configuring Location Settings (CLI)
- ✓ Basic switching RJ-45 Ethernet ports quantity: 24
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 128 Gbit/s
- ✓ 1U Rack mounting Stackable
- ✓ AC Power supply included



Aprašymas

The most affordable choice for 10G migration

The XGS1930 series, a new 10G uplink smart managed switch, comes with a stylish new look and enables cloud manageability with Zyxel NebulaFlex™ technology.

Built for convenience

This smart-looking switch features an intuitive design that simplifies daily network management for SMBs.

Manage it your way!

The XGS1930 series introduces Zyxel NebulaFlex™, which allows you to easily switch between standalone mode and our license-free Nebula cloud management platform anytime with just a few simple clicks.

Don't overspend to upgrade your wired network

With Gigabit connectivity plus four 10G uplinks, the XGS1930 series is ideal for those seeking to upgrade to an easier-to-manage network—and at an affordable price.

Techninė specifikacija

Specifications	
Sandėlio grupė	Enterprise and server products > KVM > Switches > Managed [+0][-0]
Management features	
Switch type	Managed
Switch layer	L2+/L3
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Traffic classification	Yes
Traffic shaping	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
Network	
Networking standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	Yes
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	128 Gbit/s
Forwarding rate	95.2 Mpps

Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	1.5 MB
Security	
DHCP features	DHCP client, DHCP relay
IGMP snooping	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Form factor	1U
Product colour	Black
LED indicators	Yes
Performance	
Memory type	RAM / Flash
Internal memory	512 MB
Flash memory	32 MB
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (typical)	11.5 W
Power consumption (max)	23.2 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	440 mm
Depth	270 mm

Height	433 mm
Weight	3.1 kg
Packaging content	
Cables included	AC
Rack mount kit	Yes
Packaging data	
Package width	508 mm
Package depth	394 mm
Package height	90 mm
Package weight	4.58 kg
Logistics data	
Country of origin	China
Matmenys ir svoris	
Matmenys (I × P × A)	40,00cm × 10,00cm × 51,00cm
Svoris	4,65kg