



# **Datalogic Gryphon I GM4500 Handheld bar code reader 1D/2D Laser Black**

Modelis: GM4500-BK-433K1

Gamintojas: DATALOGIC

Prekės kodas: 366098

## **259.99€**

Power source type: Battery | Type: Handheld bar code reader | Wavelength: 650 nm | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: PDF417 | Input voltage: 4.5 - 14 V | Yaw reading angle: -65 - 65° | Operating temperature (T-T): 0 - 50 °C | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: GS1 DataBar Omnidirectional | Linear (1D) barcodes supported: EAN-13 | Wireless range: 50 m | Operating relative humidity (H-H): 0 - 95% | Linear (1D) barcodes supported: GS1 DataBar Expanded | Height: 166 mm | Battery capacity: 3250 mAh | Cables included: USB | Standard interfaces: RF Wireless, USB | Charging base: Yes | Battery voltage: 12 V | 2D (matrix & stacked) barcodes supported: MaxiCode | Number of reads per charge: 80000 | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417 | 2D (matrix & stacked) barcodes supported: Micro QR Code | 2D (matrix &

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

stacked) barcodes supported: GS1 DataBar Stacked Omnidirectional | 2D (matrix & stacked)  
barcodes supported: QR Code | 2D (matrix & stacked) barcodes supported: Data Matrix | Light levels  
(direct sunlight): 0 - 100000 lx | Optical sensor resolution (W x H): 1280 x 800 pixels | 2D (matrix &  
stacked) barcodes supported: GS1 DataBar Expanded Stacked | Weight: 235 g | Storage temperature  
(T-T): -40 - 70 °C | Harmonized System (HS) code: 84716070 | Tilt reading angle: 0 - 360° | Depth: 68  
mm | Operating frequency: 433 MHz | Width: 109 mm | Scanner type: 1D/2D | Sensor type: Laser |  
Battery technology: Lithium-Ion (Li-Ion) | Charging time: 4 h | International Protection (IP) code: IP52  
| Pitch reading angle: -65 - 65° | Connectivity technology: Wired & Wireless | Compliance certificates:  
RoHS | Product colour: Black

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903