



# CyberPower CP900EPFCLCD uninterruptible power supply (UPS) Standby (Offline) 0.9 kVA 540 W 6 AC outlet(s)

Modelis: CP900EPFCLCD

Gamintojas: CYBERPOWER

EAN: 4712364142468

Prekės kodas: 366233

---

## 228.99€

---

Certification: CE, EAC, RCM | Compatible operating systems: Windows 7/Vista/XP/2000/Server 2003, Linux | Package height: 335 mm | Nominal output voltage: 230 V | Surge energy rating: 405 J | Modem (RJ-11) ports: 1 | Battery recharge time: 8 h | Surge protection: Yes | EMI/RFI noise filtering: Yes | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Typical backup time at half load: 7 min | Waveform: Pure sine | Typical backup time at full load: 1 min | Form factor: Tower | Output frequency: 50/60 Hz | Number of batteries supported: 1 | Power protection features: Over power | Power protection features: Overload | Nominal input voltage: 165-265 V | Package width: 195 mm | Surge protection features: Modem | Input operation voltage (max): 270 V | Surge protection

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

features: Fax | Input frequency: 50/60 Hz | Audible alarm modes: Alarm when on battery, Low battery alarm, Overload alarm | Non-operating altitude: 0 - 15000 m | Operating temperature (T-T): 32 - 104 °F | Surge protection features: Network | Surge protection features: Telephone | Harmonized System (HS) code: 8504408590 | Operating relative humidity (H-H): 0 - 95% | Height: 275 mm | Maximum current: 10 A | Display type: LCD | Output voltage Total Harmonic Distortion (THD): 10% | UPS topology: Standby (Offline) | Power plug: C14 coupler | Power protection features: Short circuit | Power protection features: Over voltage | Depth: 230 mm | AC outlet types: Type F | Output power capacity: 0.9 kVA | Input operation voltage (min): 170 V | Operating temperature (T-T): 0 - 40 °C | Auto-restart: Yes | Audible alarm(s): Yes | Interface: USB | Storage temperature (T-T): 15 - 45 °C | Output power: 540 W | Storage relative humidity (H-H): 0 - 95% | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Housing material: Plastic | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | LED indicators: Operation | Operating altitude: 0 - 3000 m | Ethernet LAN (RJ-45) ports: 1 | Battery voltage: 230 V | USB 2.0 ports quantity: 1 | Cable length: 1.83 m | Product colour: Black | Response time: 4 ms | AC outlets quantity: 6 AC outlet(s) | Weight: 6.6 kg

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903