



be quiet! PURE POWER 12 550W power supply unit 20+4 pin ATX ATX Black



Modelis: BP001EU

Gamintojas: BE QUIET!

EAN: 4260052191163

Prekės kodas: 366303

86.99€

Power protection features: Overheating | Efficiency: 91.2% | CPU power connector (4+4 pin): Yes | Maximum input current (@220V): 5 A | Max output current (+5Vsb): 3 A | Power factor: 0.98 | Cable tie(s) included: Yes | Combined power (+5V): 120 W | Peak power: 600 W | Cables included: AC | Height: 150 mm | Power Factor Correction (PFC) type: Active | Peripheral (Molex) power connectors (4-pin): 1 | Shipping (inner) case height: 41.8 cm | Combined power (+3.3V): 120 W | Sustainability certificates: ENERGY STAR | Sustainability certificates: ErP | Width: 86 mm | Max output current (+3.3V): 20 A | Cabling type: Non-Modular | Weight: 2.3 kg | SATA power cable length: 500 mm | Package width: 133 mm | Package height: 210 mm | Motherboard power cable length: 55 cm | Package weight: 2.8 kg | Total power: 550 W | EPS version: 2.92 | Peripheral (Molex) power cable length: 800 | SATA power cable length: 800 mm | Maximum input current (@110V): 10 A | Number of SATA power connectors: 5 | Power protection features: Over power | Shipping (inner) case length: 44 cm | Products per shipping (inner) case: 6 pc(s) | Power protection features: Under voltage | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection features: Over current | Noise level: 14.6 dB | Power protection features: Short circuit | Power protection features: Over voltage | Sustainability certificates: Triman | AC input frequency: 50/60 Hz | On/off switch: Yes | Bearing technology: Rifle | CPU power cable length: 60 cm | PCI Express power connectors (6+2 pin): 2 | Warranty period: 10 year(s) | Depth: 160 mm | Power protection features: Surge & inrush protection (SIP) | Max output current (+12V1): 45.8 A | Combined power (-12V): 3.6 W | Shipping (inner) case net weight: 17.7 kg | AC input voltage: 100 - 240 V | 80 PLUS certification: 80 PLUS Gold | Combined power (+5Vsb): 15 W | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 0 - 90% | Max output current (+5V): 20 A | PCI Express power cable length: 60 cm | Purpose: PC | SATA power cable length: 650 mm | Combined power (+12V): 550 W | Storage relative humidity (H-H): 0 - 95% | ATX version: 3.1 | Number of fans: 1 fan(s) | Cooling type: Active | Mean time between failures (MTBF): 100000 h | Shipping (inner) case width: 34.5 cm | Compliance certificates: WEEE | Compliance certificates: cTUVus | Compliance certificates: RoHS | Compliance certificates: CE | Screws included: Yes | Compliance certificates: CB | Max output current (-12V): 0.3 A | Compliance certificates: Federal Communications Commission (FCC) | Product colour: Black | Package depth: 320 mm | PCI Express power connectors (12-pin): 1 | Motherboard power connector: 20+4 pin ATX | Number of +12V rail(s): 1 | Fan diameter: 12 cm | Power supply unit (PSU) form factor: ATX | Hold time: 16.64 ms | Compliance certificates: UKCA | Storage temperature (T-T): -20 - 70 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903