



DeepCool PN1000-M power supply unit (R-PNA00M- FC0B-JGEU)

Modelis: R-PNA00M-FC0B-JGEU

Gamintojas: DEEPCOOL

EAN: 6933412741237

Prekės kodas: 366334

111.99€

PCI Express power connectors (16-pin): 1 | Warnings: Avoid contact of the product with water or other liquids. | Warnings: Do not open the case - risk of electric shock. | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations. | Number of SATA power connectors: 8 | CPU power cable length: 70 cm | Power Good signal delay range: 100 - 150 ms | CPU power connector (4+4 pin): 2 | Motherboard power connector: 20+4 pin ATX | Cable tie(s) included: Yes | ATX power connector (20+4 pin): Yes | Cooling type: Active | AC input voltage: 100 - 240 V | Width: 150 mm | 80 PLUS certification: 80 PLUS Gold | Cables included: AC | Product colour: Black | AC input frequency: 50/60 Hz | On/off switch: Yes | Depth: 150 mm | Peripheral (Molex) power connectors (4-pin): 2 | Height: 86 mm | Operating temperature (T-T): 0 - 40 °C | Package type: Box | Number of fans: 1 fan(s) | Fan diameter: 13.5 cm | Purpose: PC | ATX version: 3.1 | Combined power (+5V): 120 W | Fan location: Top | Power protection features: Under voltage | Power Factor Correction (PFC) type: Active | Power protection features: Overheating | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

protection features: Surge protection | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Over power | Bearing technology: FDB | Cabling type: Fully-Modular | Total power: 1000 W | Power protection features: No load operation | PCI Express power connectors (6+2 pin): 3 | Combined power (+12V): 999.6 W | Efficiency: 90% | Power protection features: Surge & inrush protection (SIP) | Combined power (+3.3V): 120 W | Power supply unit (PSU) form factor: ATX | Combined power (+5Vsb): 15 W | Hold time: 16 ms | Mean time between failures (MTBF): 100000 h

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903