



CyberPower BR700ELCD-FR uninterruptible power supply (UPS) Line- Interactive 0.7 kVA 420 W 8 AC outlet(s)

Modelis: BR700ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271225

Prekės kodas: 366445

120.00€

Certification: CE | USB port: Yes | Output power capacity: 0.7 kVA | UPS topology: Line-Interactive | Form factor: Compact | Surge protection features: Digital Subscriber Line (DSL) | Surge protection features: Fax | Operating altitude: 0 - 3000 m | USB 2.0 ports quantity: 1 | Depth: 288 mm | AC outlets quantity: 8 AC outlet(s) | Cold start: Yes | Automatic Voltage Regulation (AVR): Yes | AC outlet types: Type E | Modem (RJ-11) ports: 2 | Surge protection features: Modem | Width: 166 mm | EMI/RFI noise filtering: Yes | Waveform: Sine | Surge protection features: Network | Surge protection features: Telephone | Housing material: Plastic | Storage relative humidity (H-H): 0 - 90% | Operating relative humidity (H-H): 0 - 90% | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): 0 - 40

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

°C | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Power protection features: Overload | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Typical backup time at full load: 2 min | LED indicators: Yes | Input operation voltage (max): 290 V | Typical backup time at half load: 6 min | Input frequency: 50/60 Hz | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Response time: 4 ms | Weight: 5.3 kg | Surge energy rating: 125 J | Display type: LCD | Surge protection: Yes | Height: 118 mm | Non-operating altitude: 0 - 3000 m | Product colour: Black | Output frequency: 50/60 Hz | Input operation voltage (min): 165 V | Battery recharge time: 8 h | Battery technology: Sealed Lead Acid (VRLA) | Compliance certificates: RoHS | Output power: 420 W | Storage temperature (T-T): -20 - 50 °C | Cable length: 1.5 m

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903