



CyberPower BR1200ELCD uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)

Modelis: BR1200ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271232

Prekės kodas: 366446

212.98€

Output power: 720 W | Cable length: 1.5 m | Product colour: Black | Storage temperature (T-T): -20 - 50 °C | Height: 118 mm | Battery voltage: 230 V | AC outlets quantity: 8 AC outlet(s) | Package height: 230 mm | Response time: 4 ms | Storage relative humidity (H-H): 0 - 90% | Surge protection features: Fax | Package width: 158 mm | Surge protection features: Modem | Form factor: Desktop | Surge protection features: Network | Operating relative humidity (H-H): 0 - 90% | Width: 166 mm | Sustainability compliance: Yes | Battery technology: Sealed Lead Acid (VRLA) | Number of batteries supported: 2 | Depth: 288 mm | LED indicators: Power | USB 2.0 ports quantity: 1 | LED indicators:

Status | LED indicators: Battery level | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

ports: 2 | USB port type: USB Type-A | Non-operating altitude: 0 - 3000 m | Input operation voltage (min): 165 V | Output operation voltage (max): 240 V | Input operation voltage (max): 290 V | Modem (RJ-11) ports: 2 | Typical backup time at full load: 2 min | USB port: Yes | Replacement battery cartridge: RBP0063 | Audible alarm(s): Yes | Battery recharge time: 8 h | Operating altitude: 0 - 3000 m | Surge protection: Yes | Automatic Voltage Regulation (AVR): Yes | Display type: LCD | Number of phases: 1 | Weight: 8.2 kg | Output frequency: 50/60 Hz | Heat dissipation: 137 BTU/h | Surge protection features: Telephone | EMI/RFI noise filtering: Yes | Waveform: Sine | Power protection features: Short circuit | AC outlet types: Type F | Housing material: Plastic | UPS topology: Line-Interactive | Output power capacity: 1.2 kVA | Harmonized System (HS) code: 8504408590 | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Typical backup time at half load: 9 min | Surge energy rating: 150 J | Input frequency: 50/60 Hz | Output operation voltage (min): 220 V | Compliance certificates: EAC | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903