



# CyberPower Tracer III VP700ELCD-FR uninterruptible power supply (UPS) Line- Interactive 0.7 kVA 390 W 4 AC outlet(s)

Modelis: VP700ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274851

Prekės kodas: 366451

---

## 112.99€

---

Certification: CE, RCM | Serial interface: Yes | Compliance certificates: RoHS | USB port type: USB Type-B | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Height: 2227 mm | Cables included: USB cable | Response time: 4 ms | Output power: 390 W | Ethernet LAN (RJ-45) ports: 1 | Storage temperature (T-T): -20 - 50 °C | AC outlets quantity: 4 AC outlet(s) | Cable length: 1.5 m | Battery recharge time: 8 h | Product colour:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Black | Weight: 5.14 kg | Form factor: Tower | Typical backup time at full load: 1 min | Operating temperature (T-T): 0 - 40 °C | Depth: 260 mm | Output power capacity: 0.7 kVA | Input frequency: 50/60 Hz | Typical backup time at half load: 10 min | Noise level: 40 dB | Manual: Yes | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Operating altitude: 0 - 3048 m | LED indicators: Yes | USB 2.0 ports quantity: 1 | Input operation voltage (min): 167 V | Operating relative humidity (H-H): 0 - 90% | Serial ports quantity: 1 | Audible alarm(s): Yes | Housing material: Plastic | Input operation voltage (max): 295 V | Storage relative humidity (H-H): 0 - 90% | Serial interface type: RS-232 | Display type: LCD | EMI/RFI noise filtering: Yes | Non-operating altitude: 0 - 3048 m | AC outlet types: Type E | Output operation voltage (max): 230 V | Waveform: Sine | UPS topology: Line-Interactive | Automatic Voltage Regulation (AVR): Yes | Maximum current: 3.04 A | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | USB port: Yes | Surge energy rating: 450 J | Surge protection: Yes | Output frequency: 50/60 Hz

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903