



# CyberPower Tracer III VP1000ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1 kVA 550 W 4 AC outlet(s)

Modelis: VP1000ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274868

Prekės kodas: 366452

---

## 125.99€

---

Certification: CE, RCM | Compliance certificates: RoHS | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Display type: LCD | Serial interface type: RS-232 | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Output operation voltage (max): 230 V | Output frequency: 50/60 Hz | Maximum current: 4.35 A | Input operation voltage (min): 167 V | USB port type: USB Type-B |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Automatic Voltage Regulation (AVR): Yes | Waveform: Sine | Serial interface: Yes | Surge energy rating: 450 J | Output power capacity: 1 kVA | UPS topology: Line-Interactive | AC outlet types: Type E | EMI/RFI noise filtering: Yes | Non-operating altitude: 0 - 3048 m | Input frequency: 50/60 Hz | Surge protection: Yes | Input operation voltage (max): 295 V | LED indicators: Yes | Height: 227 mm | Depth: 260 mm | Cables included: USB cable | Output power: 550 W | Operating altitude: 0 - 3048 m | Operating relative humidity (H-H): 0 - 90% | Typical backup time at full load: 1 min | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Ethernet LAN (RJ-45) ports: 1 | Storage temperature (T-T): -20 - 50 °C | Form factor: Tower | AC outlets quantity: 4 AC outlet(s) | Audible alarm(s): Yes | Cable length: 1.5 m | Battery recharge time: 8 h | USB 2.0 ports quantity: 1 | Product colour: Black | Weight: 6.23 kg | Noise level: 40 dB | Manual: Yes | USB port: Yes | Serial ports quantity: 1 | Operating temperature (T-T): 0 - 40 °C | Typical backup time at half load: 9 min | Housing material: Plastic | Response time: 4 ms | Storage relative humidity (H-H): 0 - 90%

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903