



# CyberPower Tracer III VP1200ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 5 AC outlet(s)

Modelis: VP1200ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274899

Prekės kodas: 366453

---

## 210.00€

---

Certification: CE, RCM | Compliance certificates: RoHS | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Operating relative humidity (H-H): 0 - 90% | Height: 281 mm | Cables included: USB cable | Manual: Yes | Automatic Voltage Regulation (AVR): Yes | Typical backup time at full load: 4 min | Typical backup time at half load: 12 min | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

alarm | Non-operating altitude: 0 - 3048 m | Output operation voltage (max): 230 V | Battery recharge time: 8 h | Surge energy rating: 450 J | Audible alarm(s): Yes | Storage relative humidity (H-H): 0 - 90% | Input operation voltage (min): 167 V | Serial ports quantity: 1 | Output frequency: 50/60 Hz | USB port: Yes | Serial interface type: RS-232 | AC outlet types: Type E | Output power: 720 W | UPS topology: Line-Interactive | Output power capacity: 1.2 kVA | USB port type: USB Type-B | Form factor: Tower | Waveform: Sine | Display type: LCD | Serial interface: Yes | Housing material: Plastic | Surge protection: Yes | Input operation voltage (max): 295 V | Maximum current: 5.2 A | Depth: 355 mm | Noise level: 40 dB | Input frequency: 50/60 Hz | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | EMI/RFI noise filtering: Yes | Weight: 9.62 kg | Storage temperature (T-T): -20 - 50 °C | LED indicators: Yes | Operating altitude: 0 - 3048 m | Ethernet LAN (RJ-45) ports: 1 | Product colour: Black | Cable length: 1.5 m | AC outlets quantity: 5 AC outlet(s) | Response time: 4 ms | USB 2.0 ports quantity: 1 | Operating temperature (T-T): 0 - 40 °C

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903