



CyberPower OLS3000ERT2UA uninterruptible power supply (UPS) Double- conversion (Online) 2 kVA 1800 W 8 AC outlet(s)



Modelis: OLS3000ERT2UA

Gamintojas: CYBERPOWER

EAN: 4712856273823

Prekės kodas: 366460

976.99€

Certification: CE, EAC | Cable length: 1.5 m | Product colour: Black | AC outlets quantity: 8 AC outlet(s) | Rack capacity: 2U | Package width: 540 mm | Form factor: Rackmount/Tower | Typical backup time at half load: 13.1 min | Output voltage Total Harmonic Distortion (THD): 5% | Audible alarm modes: Battery replacement, Low battery alarm, Overload alarm, Fault, Alarm when on battery | Manual: Yes | Efficiency (ECO mode): 95% | Built-in fan: Yes | Output operation voltage (min): 208 V | Cooling type: Active | Waveform: Pure sine | Operating temperature (T-T): 0 - 40 °C |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Non-operating altitude: 0 - 1500 m | Output operation voltage (max): 240 V | Serial interface: Yes | Heat dissipation: 682 BTU/h | Ethernet LAN (RJ-45) ports: 1 | Charging current: 1.5 A | Emergency Power Off (EPO): Yes | Rack mount kit: Yes | Power plug: Type F | Modem (RJ-11) ports: 1 | Input frequency: 50/60 Hz | Output power: 1800 W | Operating relative humidity (H-H): 5 - 95% | Input operation voltage (min): 190 V | Hot-swap battery: Yes | USB port: Yes | RS-232 ports: 1 | Number of batteries included: 2 pc(s) | Cables included: Input power cable, USB cable | Height: 88 mm | Serial interface type: RS-232 | Display type: LCD | Replacement battery cartridge: RBP0157 | Surge protection: Yes | Batteries included: Yes | Audible alarm(s): Yes | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Output voltage regulation: 1% | Storage temperature (T-T): -20 - 50 °C | Operating altitude: 0 - 1500 m | Input operation voltage (max): 300 V | Battery recharge time: 4 h | Compliance certificates: RoHS | Compliance certificates: CE | Battery technology: Sealed Lead Acid (VRLA) | Package height: 230 mm | Number of batteries supported: 3 | Weight: 19.2 kg | Depth: 430 mm | Typical backup time at full load: 3.8 min | EMI/RFI noise filtering: Yes | Battery life (max): 5 year(s) | Response time: 0 ms | Power protection features: Overload | Width: 438 mm | Harmonized System (HS) code: 8504408590 | Crest factor: 3:1 | Surge energy rating: 363 J | Output frequency regulation: 0.5 Hz | ECO mode: Yes | Battery capacity: 9 Ah | Control type: Buttons | Maximum current: 9 A | Emergency Power Off (EPO) connector: Yes | Output power factor: 0.9 | UPS topology: Double-conversion (Online) | USB port type: USB Type-B | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Battery voltage: 48 V | Output power capacity: 2 kVA | AC outlet types: C13 coupler | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Compliance certificates: EAC | Storage relative humidity (H-H): -20 - 50% | Input power factor: 0.99 | Power factor: 0.9 | Housing material: Metal

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903