



CyberPower CP1350EPFCLCD uninterruptible power supply (UPS) Line- Interactive 1.35 kVA 780 W 6 AC outlet(s)

Modelis: CP1350EPFCLCD

Gamintojas: CYBERPOWER

EAN: 4711027798578

Prekės kodas: 366462

314.00€

Ethernet LAN (RJ-45) ports: 1 | Form factor: Tower | Number of batteries supported: 2 | Battery capacity: 8.5 Ah | Product colour: Black | Output power: 780 W | USB 2.0 ports quantity: 3 | LED indicators: Yes | Cooling type: Passive | Battery voltage: 12 V | Weight: 10.9 kg | AC outlets quantity: 6 AC outlet(s) | Noise level: 35 dB | Width: 100 mm | Power protection features: Overload | Typical backup time at full load: 4 min | EMI/RFI noise filtering: Yes | Input operation voltage (max): 265 V | Warnings: Keep away from sources of fire and water. | Height: 265 mm | Automatic Voltage Regulation (AVR): Yes | Surge protection features: Fax | Auto-restart: Yes | Depth: 370 mm | Input operation voltage (min): 165 V | Surge protection features: Modem | Surge protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Digital Subscriber Line (DSL) | Waveform: Sine | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Cabling technology: 10/100/1000Base-T(X) | Modem (RJ-11) ports: 1 | Typical backup time at half load: 10 min | Power plug: C14 coupler | Number of type F outputs: 6 | Display type: LCD | Efficiency: 98.5% | Output power capacity: 1.35 kVA | Battery recharge time: 8 h | Surge protection features: Network | Surge protection features: Telephone | Serial interface: Yes | Input frequency: 50/60 Hz | Surge protection: Yes | USB port: Yes | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Sustainability certificates: RoHS | Serial ports quantity: 1 | UPS topology: Line-Interactive | Output frequency: 50/60 Hz | Nominal output voltage: 230 V

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903