



**Hikvision Value
Series DS-
2CD1083G2-
LIUF(2.8MM)PL
security camera
Bullet IP
security camera
Outdoor 3840 x
2160 pixels
Ceiling/wall**

Modelis: DS-2CD1083G2-LIUF 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422114756

Prekės kodas: 366628

104.99€

Bluetooth: No | Web-based management: Yes | Number of simultaneous live view channels: 6 channels | User access level: Administrator, Operator, User | Lens viewing angle, horizontal: 113° | Lens viewing angle, vertical: 62° | Lens viewing angle, diagonal: 134° | Password reset via email: Yes | Length: 170.8 mm | Number of cameras: 1 | Supported graphics resolutions: 2688 x 1520 |

Compatible memory cards: MicroSD (TransFlash) | Height: 66 mm | Package weight: 481 g |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Compatible memory cards: MicroSDHC | Card reader integrated: Yes | Reset button: Yes | Maximum resolution: 3840 x 2160 pixels | Package width: 216 mm | Sample rates: 8 - 16 kHz | Tilt angle range: 0 - 90° | Product colour: White | Operating temperature (T-T): -30 - 60 °C | Housing material: Metal | Minimum illumination: 0 lx | Supported graphics resolutions: 3200 x 1800 | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 3840 x 2160 | Storage temperature (T-T): -30 - 60 °C | Ethernet LAN: Yes | Built-in light: Yes | Package depth: 121 mm | Width: 69.1 mm | International Protection (IP) code: IP67 | Night vision distance: 30 m | Compatible memory cards: MicroSDXC | Supported graphics resolutions: 1280 x 720 (HD 720) | Package height: 118 mm | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Wi-Fi: No | Form factor: Bullet | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Storage relative humidity (H-H): 0 - 95% | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP, UPnP | Supported graphics resolutions: 640 x 480 (VGA) | Wide Dynamic Range (WDR): Yes | Housing material: Plastic | Bit rate: 32 Kbps - 16 Mbps | Quality of Service (QoS) support: Yes | Connectivity technology: Wired | Type: IP security camera | Protection features: Waterproof | Operating relative humidity (H-H): 0 - 95% | Weight: 285 g | Power consumption (max): 5 W | LED type: IR | Power source type: DC, PoE | Built-in microphone: Yes | Number of Privacy masking areas: 4 | Active tampering alarm: Yes | DC output voltage: 12 | Noise reduction: Yes | Audit log: Yes | Dynamic range: 120 dB | Mirror: Yes | Compliance certificates: WEEE | Voice codecs: G.711alaw | Fixed focal length: 2.8 mm | Compliance certificates: CB | Night vision: Yes | Identify distance: 7 m | Digest authentication: Yes | Image quality adjustment: Brightness | Day/night mode: Yes | Detect distance: 79 m | Compliance certificates: RoHS | Compliance certificates: CE | Maximum aperture number: 2 | Password protection: Yes | Client interoperability: iVMS-4200, Hik-Connect | Heartbeat: Yes | Placement supported: Outdoor | Progressive scan: Yes | Noise reduction technology: 3D noise reduction | Digital watermark: Yes | B/W night vision distance: 30 m | Number of languages: 2 | Sensor type: CMOS | Mounting type: Ceiling/wall | Frame rate: 15 fps | Maximum memory card size: 512 GB | Number of lenses: 1 | Image quality adjustment: Saturation | Signal-to-Noise Ratio (SNR): 52 dB | Observe distance: 31 m | Languages support: Ukrainian | Bit rate range: 16 - 160 Kbit/s | Camera shutter speed: 1/3 - 1/100000 s | DC output current: 0.41 A | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Region of Interest (ROI) encoding: Yes | Live view: Yes | Languages support: English | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Total megapixels: 8 MP | Recognize distance: 15 m | Number of sensors: 1 | Image quality adjustment: Sharpness | Angle of rotation: 360° | Audio formats supported: AAC-LC | Compliance certificates: REACH | Privacy protection: Yes | Power consumption (Power over Ethernet (PoE)): 6.5 W | **Highlight Compensation (HLC): Yes | Video compression formats: M-JPEG | Video compression**

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

formats: H.264+ | Video compression formats: H.265 | Video compression formats: H.265+ | Voice codecs: MP2L2 | Voice codecs: G.711ulaw | Voice codecs: G.726 | Voice codecs: PCM | Infrared (IR) cut-off filter: Yes | Pan range: 0 - 360° | Number of users: 32 user(s) | Video compression formats: H.264 | Voice codecs: G.722.1 | Video motion detection: Yes | Privacy masking: Yes | Built-in HDD: No

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903